WILKINSON

## MANUAL OF IONOGRAM SCALING

Third Version

Ъу

N. Wakai, H. Ohyama and T. Koizumi

October 1987

Radio Research Laboratory

Ministry of Posts and Telecommunications

Japan

#### PREFACE

"URSI HANDBOOK OF IONOGRAM INTERPRETATION AND REDUCTION, Second Edition, November 1972" (Report UAG-23) and "REVISION OF CHAPTERS 1 - 4 OF URSI HANDBOOK, 1978" (Report UAG-23A) are being widely utilized by geophysicists and engineers as the best guidebooks for the fundamental understanding of the ionosphere as well as for the scaling of ionograms. There is such an aspect, however, that their contents, being described too much in details, can not be necessarily suitable for beginners. At the same time, there is a demand for a simplified handbook which can be utilized for the short-term training of the ionogram scalers, as a matter of fact. This manual was compiled to cope with this purpose.

Even the experienced scalers are apt to be confused frequently, when they face at complicated ionograms in the procedure of scaling. The ionograms, however, whose interpretation seems to be difficult, could be easily scaled, if the deformation of traces from fundamental patterns would be mastered.

This manual has been compiled in terms of ionospheric parameters, laying emphasis on the most fundamental matters. Consequently the repetition of some parts is inevitable. As for the composition of contents, attention has been paid to the following points:

- The philosophy of interpretation and the scaling practice are generally based on the so-called "Ionogram Handbook" (URSI Handbook of Ionogram interpretation and Reduction, Second Edition, 1972, Report UAG-23) including the Revised Edition of the same (Report UAG-23A).
- 2. Examples of ionograms are selected mainly out of those from midlatitude stations. This manual, however, is expected to be useful. for those who work at high or low latitude stations.
- The idealized patterns of ionogram are shown systematically in diagrams (not in glossy prints).
- 4. The explanations corresponding to the diagrams are minimized for simplifying the contents.
- 5. The relevant knowledge necessary for understanding is also mentioned in the explanations of each parameter.

This manual has been compiled after exhaustive discussions made by the research staffs from the Ionospheric Radio Prediction Section of the Radio Wave Division as well as from the Radio Wave Observatories, Radio Research Laboratories.

We earnestly hope that this manual will be fully utilized not only by the scaling specialists but also ionospheric physicists and telecommunication engineers.

March, 1985

N. Wakai, H. Ohyama and T. Koizumi Radio Research Laboratories

#### PREFACE FOR REVISED EDITION

The Manual of Ionogram Scaling was published in March 1985 and distributed to the users at ionospheric sounding stations over the world as well as to the members of the INAG.

Since then a fairly large number of requests for the Manual and encouragement for the revised edition including comments and advices to the Manual reached the authors. The comments by Drs. R. W. Smith and A. S. Rodger of U. K. are particularly valuable, being based on thorough and careful examination over the whole pages of the Manual.

We held several times the meeting for refining the Manual during the passage of one year. The revised edition thus completed includes the following modification in the text, while the composition is basically same as the first one:

- 1. Some figures are re-drawn for avoiding misinterpretation.
- Local rules are entirely replaced by international ones.
- 3. Additional informations such as multiple and mixed reflections and the spread-F are incorporated.
- 4. Descriptions on the particle E layer are modified.

Radio Research Laboratory has authorized to publish the revised edition of the Manual and distribute it to the users as in the case of the first edition.

Again we hope that this Manual will be used as a training text for ionogram scalers and give some help to engineers or physicists who work with the ionograms.

July, 1986

N. Wakai, H. Ohyama and T. Koizumi Radio Research Laboratory

#### PREFACE FOR THIRD VERSION

The Revised Edition of the Manual of Ionogram Scaling was completed in July 1986 and more than 200 copies of it were distributed to world-wide ionospheric sounding stations, World Data Centers and a lot of users upon requests.

After the publication of the Revised Edition, we have found out several careless mistakes in typescript.

In last February, the IPS experts of Australia have sent us very kindly comments and suggestions, pointing out inaccurate or inappropriate notations and expressions through careful examinations of the whole text.

Thus we have challenged again to refine the Manual by replacing more than 70 pages, and to publish the result as the third version.

Some comments by IPS experts, however, have not been reflected on the version, because we have considered that they might be based on the local rules used at IPS.

In order to make easy to find out the pages retyped or modified in the text of the Revised Edition, they are marked by  $\widehat{R}$  at their inner bottom corner.

We wish to express sincere thanks to Dr. P. J. Wilkinson and experts at the IPS Radio and Space Services for their valuable contributions.

October 1987

N. Wakai, H. Ohyama, T. Koizumi Radio Research Laboratory

#### EXPLANATION

This manual contains about 160 examples of the ionograms which are usually observed in the middle latitude region. In order to facilitate users' understanding, the frequency axis of ionograms is indicated by the linear scale, and hence the logarithmic scale is applied only for the reduction of the M factor.

The compilation is made in the following order:

- 1. Simplified model ionogram.
- 2. Definition on all qualifying and descriptive letters used for the ionogram scaling.
- 3. Accuracy Rules for Individual Measurements.
- 4. All ionospheric parameters to be reduced in conformity with the URSI Ionogram Handbook are explained one by one in the following order:

fmin, foE, h'E, foEs and h'Es, type of Es, fbEs, foFl, h'F, h'F2, foF2, fxI and M factor.

These ionospheric parameters are made up of the following contents:

1. The form of description for each parameter has been unified, i.e., on the first page, the definition of parameter, scaling accuracy, indication of scaled value, and notices for scaling are put in order, together with concrete examples. Concerning the Es reflection in particular, the distinction of traces, classification of types and decision of fbEs are incorporated.

- 2. The pages following the first page of each parameter should be used in pairs, i.e., 4 examples of typical observation are illustrated on the left page and explanations corresponding to such examples are given on the right page. By way of reference, the correct value to be scaled is indicated on the right margin of each ionogram.
- 3. The description in the explanation on the right pages are divided into 3 parts. As for the "Observation", the appearance conditions of trace are described briefly, and as for the "Interpretation" it is explained how to interpret the traces appearing in the ionogram and moreover how to obtain the scaled values which seem to be most adequate for the parameters. Finally as for the "Comment", the comments or reference items concerning the interpretation, such as the way of distinguishing the confusing letters or traces, are indicated partially by means of diagrams, and in addition the origin of quotation from ionogram handbooks referred to is also indicated clearly.

#### HOW TO USE THIS MANUAL

When one can not find the way to interpret an ionogram, it is recommended to take procedures as follows:

- # Open the page where the parameter in question is dealt with.
- # Find out an illustration which is most similar to the ionogram in question.
- # Read carefully the corresponding explanations on the right page.
- # Decide the scaled value based on correct interpretation.

It is further recommended to read through pages of the other parameters relating to the parameter in question.

#### UNIT, SYMBOL & REFERENCES

- # In scaling the final numerical values concerning the frequency,
  the correct indication is to omit the decimal points (e.g. 7.0 MHz

  70).
- # Only one alphabetical letter applied should be the descriptive letter.


  In the presence of two letters, the first one is the qualifying

  letter and the second one is the descriptive letter (e.g. 315US).
- # Notes on abbreviations of References.
  - I.H. --- Ionogram Handbook (URSI Handbook of Ionogram Interpretation and Reduction, Second Edition, 1972, Report UAG-23)
  - R.H. --- Revised Handbook (Revision of Chapters 1-4 of Ionogram Handbook, 1978, Report UAG-23A),

# Contents

		Page
Example of typica	al ionogram (idealized)	
Qualifying and De	escriptive Letters	2
Accuracy Rules fo	or Indivídual Measurements	3
fmin	Definition and Scaling	5
	Diagrams and Explanations $(1 - 8)$	6
foE	Definition and Scaling	10
	Diagrams and Explanations (1 - 20)	12
h'E	Definition and Scaling	23
	Diagrams and Explanations $(1 - 8)$	24
foEs and h'Es	Definition and Scaling	28
	(How to distinguish between foEs and fxEs)	
	Diagrams and Explanations $(1 - 24)$	32
Es types	Classification of Es types	44
	Diagrams and Explanations (1 - 12)	46
fbEs	Definition and Scaling	<del></del> 52
	(How to decide fbEs)	
	Diagrams and Explanations (1 - 20)	56
foF1	Definition and Scaling	67
	Diagrams and Explanations (1 - 12)	68
h'F	Definition and Scaling	<del></del> 75
	Diagrams and Explanations $(1 - 12)$	76
h'F2	Definition and Scaling	83
	Diagrams and Explanations (1 - 8)	84

		Page
foF2	Definition and Scaling	 89
	(Extrapolation)	
	Diagrams and Explanations (1 - 20)	 92
fxI	Definition and Scaling	 102
	Diagrams and Explanations (1 - 8)	 104
M factor	Definition and Scaling	 109
	(How to obtain graphically the M factor)	
	(Scaling practice of the M factor from the ionogram with logarithmic frequency scale)	
	Diagrams and Explanations $(1 - 8)$	 114
Appendix 1	Multiple and Mixed Reflections	 118
Appendix 2	Spread F and fxI Scaling	 119



The ionogram is a record of ionospheric conditions indicated by the relationship between the frequency of radio pulse emitted upward and the virtual height of echoes reflected from the ionosphere. In the case of the normal ionogram, the frequency range covers  $1-20~\mathrm{MHz}$  and the height range covers  $0-1000~\mathrm{km}$ .

The radio waves are reflected from the ionosphere after penetrating more deeply into the ionosphere as the frequency increases. In the frequency range close to the highest plasma frequency of the ionospheric layers, the radio echoes are observed being split into two traces (the ordinary and extraordinary components corresponding to lower and higher frequency traces respectively, which are separated by about fB (electron gyro-frequency)/2), owing to the presence of the geomagnetic field. For example, foF2 and fxFl stands for the ordinary wave critical frequency of the F2 layer and the extraordinary wave critical frequency of the F1 layer respectively.

The height scale of ionogram is marked on the assumption that the radio waves propagate in the ionosphere at the speed of light. As a matter of fact, however, they propagate more slowly in such an ionized medium as the ionosphere. Therefore, the recorded heights always tend to be higher than the real heights of reflection. Thus the recorded height refers to the virtual heights (h') which are indicated as h'E, h'F etc. layer by layer.

### Qualifying and Descriptive Letters (R.H.pp.34-35)

- A \_ Qualifying letter: less than. Used only with fbEs. (See section 3.1.) Descriptive letter: Measurement influenced by, or impossible because of, the presence of a lower thin layer, for example, Es.
- B Measurement influenced by, or impossible because of, absorption in the vicinity of fmin. C Measurement influenced by, or impossible because of, any non-ionospheric reason.
- D Qualifying letter: greater than.

  Descriptive letter: Measurement influenced by, or impossible because of, the upper limit of the frequency range in use.
- E Qualifying letter: less than.

  Descriptive letter: Measurement influenced by, or impossible because of, the lower limit of the frequency range in use.
- F Measurement influenced by, or impossible because of, the presence of frequency spread.
  G Measurement influenced or impossible because the ionization density of the layer is too small to enable it to be made accurately.
- H Measurement influenced by, or impossible because of, the presence of stratification.
- I Qualifying letter only: Missing value has been replaced by an interpolated value.
   J Qualifying letter only: Ordinary component characteristic deduced from the extraordinary component.
- K Particle E layer present.
- L Measurement influenced or impossible because the trace has no sufficiently definite cusp between layers. Mixed spread F present (see section 2.8.)
- M Interpretation of measurement questionable because ordinary and extraordinary components are not distinguishable. Qualifying letter: Used with descriptive letter which shows why components not distinguishable. Descriptive letter: Used when interpretation is doubtful and a qualifying letter needed for
- other reasons (e.g., U, D, E).
- N Conditions are such that the measurement cannot be interpreted.
  O Qualifying letter: Extraordinary-component characteristic deduced from the ordinary component. (Used for x characteristics only.) Descriptive letter: Measurement refers to the ordinary component.
- P Man-made perturbations of the observed parameter; or spur type spread F present (see section 2.8).
- Q  $\sim$  Range spread present. (See also Section 2.8) R  $\sim$  Measurement influenced by, or impossible because of, attenuation in the vicinity of a critical
- S Measurement influenced by, or impossible because of, interference or atmospherics. T Qualifying and descriptive letter: Value determined by a sequence of observations, the actual observation being inconsistent or doubtful. (See section 6.9.).
- U Qualifying letter only: Uncertain or doubtful numerical value.
- V Forked trace which may influence the measurement.
- W Measurement influenced or impossible because the echo lies outside the height range recorded.
- X Measurement refers to the extraordinary component.
- Y Lacuna phenomena (also Section 2.75) or severe F-layer tilt present.
- Z Qualifying letter: Measurement deduced from the third magneto-electronic component. Descriptive letter: Third magneto-electronic component present.

In Chapter 3 the use of each letter is discussed in detail.

The following descriptive letters are used to show spread F types where spread F types are tabulated in the Standard F tables. They then take precedence over all other letters. (See section 3.2, p. 74).

- F Frequency spread present, foF2 and fxI tables only.
- L Mixed spread present. foF2 and fxI tables only.
- P Polar spur.fxI table only.
- Q Range spread present. h'F, h'F2 tables. Rarely in foF2 or fxI tables.

# Accuracy Rules for Individual Measurements (R.H.pp.31-34)

2.21. General: The accuracy rules give the desirable accuracy applicable when the structure of the ionosphere and characteristics of the ionosonde permit. They also indicate the extent of the uncertainty permitted for doubtful or extrapolated values and enable such values to be identified. The rules imply that, in general, the reliability of data is determined by the percentage inaccuracy allowed except when this percentage is less than the reading accuracy  $\Delta$ . The general properties of the rules are illustrated in Fig. 2.1, which shows, in graphical form, the rules applicable to all critical frequencies with reading accuracies  $\Delta$  = 0.1 MHz and  $\Delta$  = 0.05 MHz.

It must be remembered that the accuracy rule limits apply to reasonable doubt, not to absolute certainty. Thus, if an F trace shows some scattered echoes beyond the limit range and is such that it is unlikely that foF2 is really above the limit range. A numerical value for foF2 should be scaled. The scattered traces are scaled in accordance with the rules of section 2.83.

- 2.22. Conventions for assigning the level of accuracy: The maximum reading unit  $\Delta$  has been defined in the table of recommended reading values given above (section 2.13). Numerical values whose reliability is influenced by certain phenomena are qualified by symbols (section 2.3) according to the following rules.
  - (a) If the estimated uncertainty of a value does not exceed  $\pm$  2%, or  $\pm$   $\Delta$ , whichever is greater, then the numerical value is unqualified.
  - (b) If the estimated uncertainty of a value exceeds ± 2%, or ± Δ, whichever is greater, but does not exceed ± 5%, or ± 2 Δ, whichever is greater, the value is considered doubtful and the qualifying letter U is used with the number together with the descriptive letter which most nearly represents the reason for the uncertainty.
  - (c) If one boundary is certain and the other possible boundary of uncertainty lies within  $\pm$  10%, or  $\pm$  3  $\Delta$ , whichever is greater from it, the most probable value is taken as being midway between the observed limits, and the qualifying letter U is used with the number and appropriate descriptive letter.
  - (d) When the possible error exceeds that in paragraph (b), but it is estimated that the true value lies within 20%, or 5 Δ, whichever is greater, of an observed boundary of possible positions of the principal echo, then this observed limit is tabulated with the qualifying letter D or E, whichever is applicable, and with the appropriate descriptive letter.
  - (e) When the extreme limit of the principal echo is judged to differ from the true value of the parameter by more than 20%, or 5  $\Delta$ , whichever is greater, a descriptive letter only is tabulated without a numerical value. A descriptive letter used in this context is often termed a replacement letter (See Section 2.3).

The rules for frequencies are summarized in Fig.2.la.

- 2.23. Accuracy rules in total range of uncertainty forms: Operators who prefer to consider the total range of uncertainty may use the following rules which are equivalent to those given above.
  - (a) If the total range of uncertainty does not exceed 4% or  $2\Delta$ , whichever is greater, then the numerical value is unqualified.
  - (b) If the total range of uncertainty exceeds 4% or 2Δ, whichever is greater, but does not exceed 10% or 4Δ, whichever is greater, the value is considered doubtful and the qualifying letter U is used with the most probable value together with the descriptive letter which most nearly represents the reason for the uncertainty.
  - (c) If one boundary is certain and the other possible boundary lies within 10% or 3∆, whichever is greater from it, the most probable value is taken as being midway between the observed limits, and the qualifying letter U is used with this value and the appropriate descriptive letter.
  - (d) When the total range of uncertainty exceeds that in paragraph (b) but is less than 20% or  $5\Delta$ , whichever is greater, of an observed boundary of possible positions of the principal echo trace, then this observed limit is tabulated with the qualifying letter D or E, whichever is applicable, and the appropriate descriptive letter.
  - (e) When the total range of uncertainty exceeds 20% or  $5\Delta$ , whichever is greater, a descriptive letter only is tabulated without a numerical value.

The application of these rules to F-region frequency parameters  $\Delta$  = 0.1 MHz and E-region parameters with  $\Delta$  = 0.05 MHz are shown graphically in Figs. 2.1 (a) and (b), respectively."




Fig. 2.1a Accuracy rules for F region frequencies  $\Delta$  = 0.1 MHz in terms of total range of error.




Fig. 2.1b Accuracy rules for E region frequencies  $\Delta$  = 0.05 MHz in terms of total range of error.

# fmin

<u>Definition</u>: fmin (minimum frequency) is the lowest frequency of reflection wave recorded in the ionogram.

## @ Scaling accuracy :

fmin is scaled at the accuracy of 0.1 MHz (e.g. 1.6 MHz)

### @ Indication of scaled value :


fmin is indicated by a numerical value in unit of 0.1 MHz with or without letters or by a letter only.

#### (Examples)

- C --- Numerical values cannot be obtained because of the defect of the ionosonde.
- 16C --- C is a descriptive letter.
- 46EC --- E is a qualifying letter, C is a descriptive letter.

### @ Notices for scaling :

- In the actual scaling it is recommended that the lowest frequency of the first order reflection trace recorded in its ionogram be scaled. It is seldom that fmin has to be scaled either from the extraordinary waves or Z components. In the case of the scaling from the Z component, a descriptive letter Z should be given to its numerical value (e.g. 16Z).
- The very weak reflections should be ignored.
- 3. When fmin is high a normal trace may look very weak. But it should be treated as a strong trace from which fmin is scaled in a usual way. The strength of absorption can be deduced from the value of fmin.
- fmin must not be scaled from the d type Es trace (a weak diffuse trace at a virtual height below 95 km : see Case 9 of Es type), not from traces reflected obliquely or traces appearing suddenly and/or changing rapidly.



1

Observation: The ionogram usually seen in the summer daytime.

The normal E, F1, F2 layers and the c type Es layer are observed.

Interpretation: The lowest frequency of the traces in this ionogram is 1.8 MHz.

fmin = 18

Comment:

In the case where the condition of the ionosphere is undisturbed and the ionosonde works normally, the value of the daytime fmin will be approximately between 1.5 to 2.0 MHz. Increase in fmin due to the decrease in the sensitivity of ionosonde must not be confused with that due to the increase in absorption. In these cases, the descriptive letter expressing the malfunction of the ionosonde should be attached (e.g. fmin = 25EC).

(2)

Observation: The trace below 4.8 MHz disappeared owing to the high absorption ( E and Fl layer traces are not visible ).

Interpretation: The frequency of fmin is high when the absorption is strong. fmin is important as a parameter which indicates the degree of absorption. fmin of this ionogram is expressed simply with numerical values.

fmin = 48

Comment: The absorption is rarely observed in the nighttime at midlatitude.

(3)

Observation: No trace is observed on the ionogram. There is almost no interference.

Interpretation: This is the case where the absorption condition is stronger than that in Case 2. When the ionosonde works normally, the black-out on ionogram is caused by the sudden ionospheric disturbances (SID). As the SID progresses, the disappearance of the trace starts very quickly from the lower part of frequency. The recovery usually occurs slowly from the higher part of frequency. All parameters are indicated by the letter B, including fmin but excluding Es types.

fmin = B


4

Observation: The trace below 3.6 MHz is not recorded owing to the defect of the ionosonde. Both the second order reflection of Es layer and the Fl layer not fully developed are visible.

Interpretation: The frequency band below fmin is affected by the defect. Therefore, the numerical value should be accompanied by the qualifying letter E and the descriptive letter C.

fmin = (fmin)EC = 36EC

Comment: When the cause is ascribed to the interference, the descriptive letter S is used instead of C.



(5)

Observation: A normal ionogram observed in the nighttime. Only the F layer trace appears from the lowest frequency of the ionosonde.

Interpretation: It is interpreted that the trace extends down to below the lowest frequency 1.0 MHz of the ionosonde. Therefore, both the qualifying letter E (less than) and the descriptive letter E ( below the lower limit of frequency ) should be given to the numerical value 1.0 to be more accurate, but the use of only the descriptive letter E may be allowed for simplification.

fmin = 10EE

**6** 

Observation: The F layer trace is observed from 1.1 MHz and the f type

Es is seen at the height of 110 km.

Interpretation: The lowest frequency 1.1 MHz of the trace recorded on the ionogram is regarded as fmin.

fmin = 11



Observation: Below 1.6 MHz, the trace is not observed owing to the interference caused by the broadcasting wave.

Interpretation: Every sounding station is exposed to the interference during hours just before sunset to at least midnight and after sunrise.

If there were no interference, the trace would be observed down to below 1.6 MHz. The value of the lowest frequency of trace should be accompanied by the qualifying letter E ( less than ) and the descriptive letter S (interference).

fmin = (fmin)ES = 16ES



Observation: The f type Es is observed up to the third order reflection.

The lowest frequency (fm2) of the second order reflection is lower than that (fmin) of the first order reflection.

fm2 = 1.5 MHz


Interpretation: Since the second order reflection suffers from much more absorption than the first order one, the ionograms such as this example can rarely be observed. In the normal scaling, fmin should be scaled from the first order reflection, rather than from the second one.

fmin = 18



@ Definition : foE is the ordinary wave critical frequency of the lowest thick stratification in the E region. [According to the magnetoionic theory, the frequency separation between the ordinary and extraordinary mode traces is equal to about fB/2, where fB is the gyro-frequency (the frequency at which the electrons gyrate around the geomagnetic field). The value of fB varies depending on the location of the station and the ionospheric height concerned. In middle latitudes, it is about 1.2 MHz].

> foE is closely related to the solar zenith angle, having usually the highest value around the local noon in smooth diurnal variation.



## @ Scaling accuracy :

foE should be scaled with an accuracy of 0.05 MHz. Therefore, the last digit of scaled value is always 0 or 5 (e.g. 2.00 MHz, 3.15 MHz).

#### @ Indication of scaled value :

foE is expressed by a numerical value with or without letters, or by only a descriptive letter according to the accuracy rule.

(Examples)

S --- No numerical value can be obtained owing to the interference.

315R --- R is a descriptive letter which expresses the attenuation around the critical frequency.

300UR --- U is a qualifying letter (uncertain).


#### @ Notices for scaling :

The time of appearance and disappearance of the normal E layer varies with the season and the latitude of the station. foE should always be scaled during this time interval. It is convenient for

scalers to know beforehand the time interval for each month in reference to the past data.

- 2. Before sunrise, such stratifications as the h or c type Es and the E2 layer are observed in the E region prior to the development of the normal E layer. These traces must not be confused with the normal E layer. The h or c type Es and the E2 layer are usually observed with a virtual height greater than that of the normal E layer. In particular the short-lived E2 layer appears in the vicinity of about 150 km. The E2 layer as well as the normal E layer shows the retardation at the highest frequency.
- 3. If the particle E layer is observed, the value of foE should be scaled even in the nighttime and denoted in the table with the descriptive letter K.

## foE-1



## foE-1

Observation: Ionogram in quiet ionosphere. The Es and Fl layers are not observed.

Interpretation: foE is to be determined in consideration of the shape of retardation of the E region trace. foE is nearly equal to the lowest frequency of the F layer trace.

foE = 210

Comment: Since the extraordinary component is usually characterized by larger absorption than that for the ordinary component, sometimes the trace becomes weak or not visible at all.

In cases where the retardation cusp of the trace near fxE is missing, care should be taken not to confuse with an

Es layer trace.

2 Observation: A cusp is visible near 2.5 MHz of the E layer trace. The Fl layer does not develop sufficiently.

Interpretation: The cusp near 2.5 MHz is caused by an underlying stratification (see R.H. p. 83, letter H). Therefore, foE should be accompanied by the descriptive letter H which expresses the influence by the stratification.

foE = (foE)H = 320H

Comment: The retardation cusp appears also at the lower end of the F region trace. The cusp of the E region which usually appears first in the vicinity of foE moves toward the lower frequency, becoming weak with the passage of time. When the lower cusp is widely separated from foE, it is not necessary to attach the descriptive letter H. In this case, H should be applied

to h'E.

Observation: The trace of the E2 layer is observed between the normal E and F layers. The F1 layer does not exist.

Comment: The appearance of E2 layer should be remarked in an appropriate column of the scaling table. The E2 layer is transient and thick layer which appears between the normal E layer and the F layer, and it is mainly observed for 1 - 2 hours around sunrise and sunset hours. The other traces than those of the particle E layer observed in disturbed conditions can be regarded as the E2 layer ( see I.H. p.17 ).

Observation: Below 1.6 MHz, no trace is observed owing to the interference.

Some cusps are observed in the E region.

Interpretation: Ionograms like this are seen early in the morning. The virtual height of the E region traces is too high to be the normal E layer. It could be identified from an examination of a sequence of records or from the diurnal trend of foE values. Since the normal E layer is considered to be masked by the interference,

foE = S.

Comment: If it can be judged from the sequential check of records that foE exists near fmin, foE may be deduced from the retardation of the lower part of traces but care should be taken to ensure that the cusp is not associated with an E2 layer.

foE = 160ES

,		
(5) Cusp except foE is observed in E layer traces	fmin	15 280UA
1 2 3 4 5 6 7 8 9 10 11MHz 400	foE h'E foEs	110 30JA
300	fxEs h'Es Es type	36 115 cl
200	fbEs foFl	28
	h'F h'F2 foF2	215 58
fmin cusp foE	fxI	70
6 E region traces are blanketed by Es layer	fmin	16
400	foE h'E foEs	300UA A 40JA
300	fxEs h'Es Es type	46 105 l2
200	fbEs foFl	30 45L
100	h'F h'F2 foF2	220 295 66
fmin foE	fxI	
7 E region traces are blanketed by Es layer	fmin	15
400	foE h'E foEs	350UA A 57JA
300 3Es	fxEs h'Es	63 100
200 2Es	Es type fbEs foFl	<b>ይ3h1</b> 35
100 Es-h Es- Ł	h'F h'F2	270
fmin foE fxEs	foF2 fxI	60
8 No traces are observed near foE	fmin	16
\(\frac{1}{200}\)	foE h'E foEs	365UR 100 46
300	fxEs h'Es Es type	52 150 hl
200	fbEs foFl h'F	42 50 200EA
100	h'F2 foF2	200EA 290 92
fmin foE foEs	fxI	

Observation: A small cusp is observed near 2.4 MHz which is separated from fminF by about 0.4 HMz.

Interpretation: The normal value of foE is 2.8 MHz (dotted lines). The cusp at 2.4 MHz is considered to be produced by stratification. In this case it is interpreted that the vicinity of foE is blanketed by the c type Es. In consideration of the lower part of the F layer trace, the value of foE can be obtained by extrapolation. If necessary, a letter is applied according to the accuracy rule.

foE = 280UA

6 Observation: Only the & type Es is observed in the E region. The retardation is observed at the lower end of the F layer trace.

Interpretation: The normal E layer is blanketed by the & type Es.

Judging from the shape of the lower part of the F layer trace,
it can be inferred ( dotted curve ) that foE is nearly same as
fbEs. However, care should be taken to ensure that the F layer
retardation is not caused by the presence of an E2 layer.

foE = (fbEs)UA = 300UA

Comment: In this case, fbEs, which is usually plotted by dots in the f-plot diagram, should be plotted by an open circle.

Observation: The normal E layer is completely blanketed by the & type Es.

The ordinary wave component of the h type Es is observed at the height of 140 km. The retardation is not observed in the low frequency part of the F layer trace, in contrast to Case 6.

Interpretation: foE should be close to the low frequency end of the h type Es ( dotted curve ). Being based on the same interpretation as Case 6, foE can be obtained from the shape of retardation in the low frequency part of the h type Es.

foE = 350UA

In the case of no retardation,

foE = A.

Observation: The trace is lost in the frequency range of the vicinity of foE. The h type Es is observed.

Interpretation: The disappearance of trace in the vicinity of foE is not caused by the interference. Therefore, the attenuation can be regarded as the cause. foE must be in this part and so it can be obtained by extrapolating the traces. If necessary, the accuracy rule is to be applied. The indication of scaled value is adequately decided by the width of frequency range of the disappeared trace.

foE = 365R, 365UR, 350DR or R

Comment: In the case of interference, R is replaced by S. As for the accuracy rules, see pp. 3-4 of this manual.

9 E layer traces are not clear owing to the inter- ference	fmin	16ES
1 2 3 4 5 6 7 8 / 9 10 11MHz	foE	S
km $l$	h¹E	S
400 SEs	foEs	48JA
	fxEs	54
300	h'Es	110
The last last last last last last last last	Es type	c3
200   0   0   0   0   0   0   0   0   0	fbEs	42
enc	foFl h'F	<b>ΛΕΕΤΙ</b> 1
100	n'r h'F2	255EA
	foF2	80
	fxI	00
fmin fbEs fxEs	TVT	
		_
do to the interference	fmin	16ES
	foE	S
1.00 H.	h'E	S
400	foEs	16ES
	fxEs	~
300 + + + + + + + + + + + + + + + + + +	h'Es	S
	Es type	16ES
300 errenoe	fbEs	TOPD
	foFl h'F	220
100	h'F2	220
100	foF2	38
	fxI	50
fmin foF2	171	
O N. L		
lower part of the F layer		26
	fmin foE	36 B
	h'E	В
400	foEs	36EB
	fxEs	ريون ر
300	h'Es	В
	Es type	
absorption	fbEs	36EB
200	foFl	
	h'F	245
	h'F2	
	foF2	57
fmin foF2	fxI	
Only the extraordinary component of the E layer is visible	fmin	35EC
	foE	320JC
	h'E	5200C
400	foEs	Ğ
	fxEs	
300	h'Es	G
	Es type	
200	fbEs	G
200 +	foFl	上(44)
	h'F	250
	h'F2	275
	foF2	68
	fxI	
fmin - fxE		

9 Observation: Below 1.6 MHz the trace is not clear owing to the interference. Es is of the c type and it can be seen up to the

third order reflection. foEs = 4.8 MHz

Interpretation: Judging from the retardation of the lower part of the c type Es, foE is considered to be present in the interference range. The numerical value cannot be scaled and so it is expressed by the letter.

foE = S

(10) Observation: Below 1.6 MHz the E region trace is not clear owing to the interference.

Interpretation: This ionogram is frequently seen early in the morning or after sunset. In the diagram, foE can be presumed from the retardation of the lower part of the F layer trace (see Case 6).

foE = 150US

Comment: When no retardation is seen in the F layer trace, foE is scaled as smaller than fmin or expressed only by the letter.

foE = 160ES or foE = S

Observation: Below 3.6 MHz all the traces disappeared owing to the strong absorption (SID).

Interpretation: The absorption caused by the solar flare always occurs in the daytime. Even when the E layer trace is not visible, the column for foE must be filled in.

foE = B

Comment: In the case where the retardation is seen in the low frequency part of the F layer trace and the value of foE can be inferred from fmin F, as in Case 6.

If the cause of missing traces is interference (S) or a defect of the ionosonde (C), S or C is used instead of the letter B.

0bservation: The traces below 3.5 MHz including the ordinary component of the E layer trace are missing owing to the defect of the ionosonde.

fxE = 3.80 MHz

Interpretation: Since fxE is clear, foE is obtained by subtracting fB/2 from fxE. foE should be accompanied by the qualifying letter J and the descriptive letter C.

foE = (fxE - fB/2)JC = 320JC

Comment: Concerning the separation between foE and fxE, see Definition of foE on p.10.

13) The trace near foE is an abnormal shape ( $\lambda$ type)	fmin	15
1 2 3 4 5 6 7 8 9 10 11MHz	foE h'E	255
1400 Land	foEs	105 34
	fxEs	40
300	h'Es Es type	115 e2
200	fbEs	25EG
200	foF1	01 =
100	h'F h'F2	245
	foF2	53
fmin foE foEs	fxI	
foE exists below the lowest frequency of the ionosonde	_	
ionosonde	fmin foE	10EE 100EE
	h'E	E
400	foEs fxEs	26JA
300	h'Es	32 100
	Es type	l l
200	fbEs foFl	E
	h'F	250
100	h'F2 foF2	64
	fxI	04
fmin fxEs		
(15) Several cusps are present near foE	a 1	
	fmin foE	17 265
400	h'E	11C
	foEs fxEs	44 50
300	h'Es	165
	Es type	h2
200	fbEs foFl	35 L(40)
100	h 'F	A
	h'F2 foF2	270 68
fmin foE foEs	fxI	00
	:	
16 Two Es types are visible near foE	fmin	15
	foE h'E	345UA 110
400	foEs	40
300	fxEs h'Es	46 125
	Es type	hlcl
200 Es-h	fbEs foFl	38 <b>L</b>
Es-c	h'F	245
100	h'F2	L
	foF2 fxI	69
fmin foE foEs		

0bservation: The normal E layer is connected to the c type Es with a  $\lambda$ -shaped overlapping of the retarded part of trace.

Interpretation: This shape is considered to be produced by simultaneous occurrence of the reflection by the normal E layer and the oblique reflection from the Es layer.

foE = 255

Comment: A comment should be included with the scaled values for such

Observation: Ionogram at sunrise. The retardation is visible in the lower part of the F layer trace. The Es is of the  $\ell$  type.

foEs = 2.6 MHz

Interpretation: The retardation of the lower part of the F layer trace shows that the normal E layer is present below fmin. Since the trace is appearing from the lower frequency (1.0 MHz) of the ionosonde, foE and h'E are expressed by the descriptive letter E.

foE = 100EE

(15) Observation: Two cusps are visible near foE (2.65 MHz and 3.05 MHz). The Es is of the h type. foEs = 4.4 MHz

Interpretation: This kind of echo pattern which is likely to appear in summer morning frequently causes confusion in determining foE. foE should be decided in consideration of a sequence of ionograms (the f-plot is effective). In this ionogram the cusp at 2.65 MHz corresponds to foE, while the cusp at 3.05 MHz which is connected with the h type Es is considered to be the cusp by a different stratification.

foE = 265

Observation: The trace in the E region shows the cusp by the frequency of 3.25 MHz and two Es layers of different types are observed.

foEs = 4.0 MHz and 3.6 MHz

Interpretation: The lowest frequency 3.45 MHz of the h type Es trace is the real foE. In this case the c type Es of 3.3 - 3.6 MHz is blanketing in the vicinity of foE. The interpretation given for Case 5 is also applicable to this case.

foE = 345UA

	<u> </u>		
(17)	The particle E layer is appearing	fmin	13
	1 2 3 4 5 6 7 8 9 10 11MHz	foE	170K
km	1 2 3 4 5 6 7 8 9 10 11MHz   1	h'E	135K
400 -		foEs	17K
		fxEs	23K
300		h'Es Es type	135K kl
		fbEs	17K
200 -		foFl	1 ++
100		h 'F	250
100		h'F2	מי די מי
		foF2 fxI	51F 60
fm	in foE foF2	171	00
18	Only the extraordinary component of the particle		3 0300
<u> </u>	E layer is visible	fmin foE	loee 090JK
		h'E	0905 K
400 -		foEs	09JK
		fxEs	15K
300 -		h'Es	E
		Es type	kl oor
200		fbEs foFl	09K
		h'F	255
100		h'F2	-//
		foF2	36
		fxI	42X
	n fxE		***************************************
(19)	The ordinary component of the particle E layer is not clear owing to the interference		
	Not creat owing to the interior	fmin foE	20ES 200JK
		ioв h'E	2003 K
400		foEs	20JK
	int	fxEs	26K
300		h'Es	S
	rferenc	Es type	kl
200		fbEs	20K
		foFl h'F	240
100		h'F2	5
		foF2	57 63x
	fmin fxE	fxI	63X
(30)	The r type Es is appearing ( High latitude iono-		
20)	gram sample )	fmin	12
		foE	250UK
400		h'E	A 40F
700	fminF / /:/::'	foEs fxEs	46F
300		h'Es	110
500		Es type	rlkl
202		fbEs	25UK
200	Ø Ø Es−r	foFl	050
100		h'F	250
100		h'F2 foF2	69F
		fxI	77
fn	in foE foEs fxI		1 1

(17)

Observation: Ionogram at night. The particle E layer (foE = 1.70 MHz) is observed. h'E= 135 km. The F layer traces are weakly spread near the critical frequency.

Interpretation: The particle E layer is produced by the precipitating particles into the lower atmosphere during ionospheric disturbances, showing larger virtual height than that of the normal E layer. foE usually agrees with fminF.

$$foE = (foE)K = 170K$$

Comment: The letter K stands for the particle E layer. When the particle E layer appears, foE and h'E should be written in the tabulation sheet.

(18)

Observation: The F layer trace is appearing from the lowest frequency (1.0 MHz) of the ionosonde. The trace at 135 km in the E region seems to be the extraordinary wave.

Interpretation: Judging from the retardation of the low frequency part of the F layer trace, the trace in the E region is interpreted as the particle E layer. This case is substantially the same as Case 17 with the frequency scale shifted slightly. The value of fxE subtracted by fB/2 (about 0.6 MHz) is marked with the letter JK.

foE = (fxE - fB/2) = 090JK

Comment:

Both the descriptive letter K (particle E layer) and E (less than the lowest frequency) are applicable. But the priority is given to K rather than E. Concerning the separation between foE and fxE, see Definition of foE on p.10.

(19)

Observation: The extraordinary wave trace from a thick layer is observed at a height of about 140 km. Traces below 2.0 MHz can not be observed owing to the interference.

Interpretation: Judging from the retardation of the lower part of the F layer traces, the trace in the E region must be the extraordinary component of the particle E layer. This case is also almost same as Case 18, when the interference is supposed to be at lowest limit of Case 18. The procedure of scaling is the same as Case 18.

foE = (fxE - fB/2)JK = 200JK

Comment: When the retardation of the F layer ordinary trace is clear, foE (particle E layer) may be scaled from this frequency.

foE = (fminF)UK = 200UK

(20)

Observation : The r type Es is observed in the E region. Weak spreads are visible both in the Es and F layer traces. foEs =  $4.0~\mathrm{MHz}$ 

Interpretation: As the penetration frequency of E region traces exceeds the lowest frequency of F layer traces, the E region trace should be the r type Es. The retardation near fminF stands for the existence of underlying particle E layer. Therefore, it can be interpreted that the particle E layer is blanketed by the r type Es.

fbEs = (fminF)UK = 25UK

Note

@ Definition : h'E means the minimum virtual height of the normal E-layer.

### @ Scaling accuracy :

h'E is scaled with an accuracy of 2 km (see R.H. p.30 section 2.13).

# @ Indication of scaled value :

h'E is indicated by a numerical value and/or letters. The letter is used according to the accuracy rule (see p. 3) as usual.

#### (Examples)

B --- No numerical value can be obtained, being affected by absorption.

100C --- C is the descriptive letter (trouble with ionosonde).

115UC --- U is the qualifying letter (doubtful).

# @ Notices for scaling :

- When the accuracy of height markers is worse than ± 5 km, h'E should not be scaled numerically.
- 2. h'E must be scaled when foE is scaled (for the whole daytime and in the presence of the particle E-layer even at night), keeping in mind that foE and h'E are not necessarily numerical values only.
- 3. The minimum virtual height of a reflected wave is scaled from the horizontal part of trace. In cases, however, where there is no horizontal part, or the trace is blanketed by an underlying layer (Es), the scaled value should be expressed with appropriate qualifying and/or descriptive letters in accordance with the accuracy rule (see p. 3).
- 4. When the particle E layer is observed, h'E is also accompanied by the descriptive letter K (see Cases 17 20 of foE).

# h'E - 1

1 Normal ionogram	fmin	16
1 2 3 4 5 6 7 8 9 10 11MHz	foE	300
	h'E	110
400	foEs	30EG
	fxEs h'Es	G
300	Es type	G
	fbEs	30EG
200 + -   -   -   -	foFl	
/ / 」 h'臣	h'F	255
	h'F2	<i>/</i> -
	foF2 fxI	63
fmin foE	1 X 1	
2 Trace is not horizontal near fmin	fmin	18
	foE	205
	h'E	120EB
400 J. SES	foEs	35
	fxEs	41
300 + 1	h'Es Es type	115
200 to 2Es 2Es	fbEs	c3 32
200   1   -   -   -   -   -   -   -   -   -	foFl	J-
nce	h'F	270A
100	h'F2	<i>.</i> -
	foF2 fxI	60
fmin foE foEs	TYT	
Chang due to underdaring stretification and		
observed in the E layer traces	fmin	16
	foE	310H
	h'E	110H
400	foEs	G
	fxEs	
300	h'Es	G
	Es type fbEs	G
200	foFl	48UL
h'E	h 'F	255
100	h'F2	295
	foF2	75
fmin cusp foE	fxI	
4 Traces of E layer and lower part of Fl layer are		
blanketed by & type Es	fmin foE	18
	h'E	A A
400	foEs	48JA
	fxEs	54
300	h'Es	100
	Es type	\$2 \\
200   2Es	fbEs foFl	40 42
	h'F	42 A
	h†F2	275
	foF2	68
	fxI	
fmin fbEs fxEs		

Observation: Normal ionogram in the daytime. No Es traces are observed.

Interpretation: h'E is scaled from the lowest part of E layer trace which is almost horizontal.

 $h^{1}E = 110$ 

- 2 Observation: Interference is severe up to 1.5 MHz. E region traces are observed from 1.8 MHz. Es of c type is observed up to 3rd order reflection.
  - Interpretation: Normal E layer trace shows the retardation. h'E is expressed by the lowest height observed, together with the qualifying letter E (less than) and descriptive letter B (absorption). h'E = 120EB
  - Comment: If there is interference up to 1.8 MHz, S is used instead of letter B.
- 3 Observation: In the vicinity of 2.5 MHz on the trace of ordinary wave component of normal E layer, other cusp than foE (3.10 MHz) is observed. No Es layer trace exists.
  - Interpretation: In the case where the cusp is close to fmin, h'E is possibly influenced. Therefore, the numerical value is followed by the descriptive letter H.
  - Comment: When the cusp is close to foE, i.e. h'E is not influenced by the presence of stratification, the descriptive letter H of h'E can be omitted but should be included on foE (see Case 2, p. 12).
- (4) Observation: & type Es is observed at the height of 100 km. Traces of normal E layer and of Fl layer below 4 MHz are not observed.
  - Interpretation: Since the ionogram is obtained at the time when foE is expected to be in the vicinity of 3.20 MHz, it is interpreted that normal E layer is blanketed by Es layer. Letter A is used.

h'E = A

# h' E - 2

	The lower part of E trace is blanketed by £ type		
(5)	E5	fmin	16
km	1 2 3 4 5 6 7 8 9 10 11MHz	foE h¹E	300
400		foEs	120EA 32
		fxEs	38
300		h'Es	140EG
		Es type	hll2 30EG
200 -	Es-h	fbEs foFl	45UL
		h'F	225
100		h'F2	275L
		foF2	80
	fmin foE foEs	fxI	
(6)	The vicinity of foE is blanketed by c type Es		
	The state of the s	fmin	17
		foE h'E	A 110
400 -		foEs	39
		fxEs	45
300 -		h'Es	115
005		Es type fbEs	cl
200 -		foFl	32 43L
1,00		h'F	225
100 -		h'F2	280
		foF2 fxI	63
	fmin cusp foEs	TYT	
(7)	E region traces are not observed owing to the		
۳	interference	fmin	16ES
		foE	S
400 -	inte	h'E	S
	671	foEs fxEs	16ES
300 -		h'Es	S
	erenc.	Es type	~
200 -		fbEs	16ES
		foFl	
100 -		h'F h'F2	210
		foF2	35
	fmin foF2	fxI	/
0	No traces are observed from E region and the lower	<del></del>	
(8)	part of the F layer	fmin	35
		foE	В
400 -		h'E foEs	В 35EB
		fxEs	J/ED
300 -		h'Es	В
	absorption	Es type	
200 -		fbEs	35EB
		foFl h'F	240
100 -		h'F2	Z-40
		foF2	66
		fxI	
	fmin foF2		

Observation : E layer traces below 2.7 MHz are blanketed by & type Es. (5)

foE = 3.00 MHz, foEs = 2.7 MHz ( $\ell$  type).

Interpretation: Only a part of normal E layer trace is observed. Since the trace near 2.7 MHz is not horizontal, h'E is considered to be lower than 120 km. Therefore, the numerical value should be followed by the qualifying letter E and the descriptive letter A.

h'E = 120EA

Comment: When the influence of blanketing by Es layer is more significant only descriptive letter A is used.

For  $\ell$  type Es layer, foEs = 27G, fbEs = 27G and h'Es = 100.

(6) Observation: The cusp near 2.8 MHz is related to foE but not foE itself. The trace from 2.8 MHz to 3.9 MHz is of c type Es.

Interpretation: The cusp observed near 2.8 MHz is to be extended as dotted line to obtain foE. It is interpreted that the proximity of foE is blanketed by c type Es. Since the traces below 2.8 MHz are of normal E layer, h'E can be scaled by numerical value.

h'E = 110

(7)Observation: This kind of ionogram is often observed early in the morning or after sunset. Below 1.6 MHz the traces are not clear owing to interference. Retardation is observed in the lower part of F layer traces.

Interpretation: Judging from the expected value of foE and from the retardation observed in the lower part of F layer traces, foE is considered to be near 1.50 MHz. Since, however. no information on h'E is obtained, it is expressed only by the symbol.

h'E = S

(8)Observation: In the region below 3.5 MHz no traces are recorded at all. Interpretation: The ionogram seen at the time of absorption. Since it is interpreted that all echoes from E region including the interference are influenced by fairly strong absorption, the letter B is used.


Comment: Descriptive letters are properly used according to the causes of disappearance of traces (e.g. C for Ionosonde trouble, S for interference, etc.).

foEs, h'Es

@ Definition : foEs is the top frequency of the ordinary wave component of continuous Es traces.

The Es-layer is a thin layer which shows rapid change and is observed in the height range from about 100 km to 170 km. In this region, any traces which cannot be clearly identified as the normal E layer or E2-layer should be always treated as Es reflections.

h'Es (the minimum height of the Es layer) is the lowest virtual height of the trace from which foEs is scaled.



### @ Scaling accuracy:

foEs is scaled with an accuracy of 0.1 MHz(e.g.  $5.3 \ \text{MHz}$ ). h'Es is scaled at the accuracy of 2 km(see R.H. p.30, section 2.13).

### @ Indication of scaled value :

foEs is expressed by a numerical value and/or letters.

(Examples)

30EG --- Es layer traces are not seen in the condition that the normal E layer is observed (Daytime). It is interpreted that Es is embedded in the normal E layer (foE = 3.0 MHz).

16ES --- E is the qualifying letter and S is the descriptive letter.

52JA --- J is the qualifying letter and A is the descriptive letter.

h'Es is expressed by a numerical value and/or letters. (Examples)

S --- The numerical value cannot be obtained owing to the interference.

150EG --- E is the qualifying letter and G is the descriptive letter.

### @ Notices for scaling :

- 1. foEs and h'Es should be scaled over the whole day.
- The following characteristics should be referred to in identifying the presence of an Es trace:
  - (1) Since Es is a thin layer, no retardation is usually observed (except r and k type in high latitudes or at mid-latitudes under disturbed conditions) near its critical frequency.
  - (2) Es layer traces are usually observed in the height range from  $100~\rm km$  to  $150~\rm km$ . But the height occasionally exceeds  $150~\rm km$  in the case of h type Es.
  - (3) Es layer is classified into one of 11 types in which 2, c, h and f types are generally observed in the middle latitudes.

These types of Es appear sometimes independently or simultaneously.

3. h'Es should be scaled at the lowest height where Es layer trace becomes horizontal.

### @ Scaling rules of Es trace :


- 1. Traces caused by oblique reflections should be ignored.
- 2. Scaling should not be based on very weak and intermittent traces.
- 3. Short-lived or rapidly changing phenomena like the meteor echoes are not to be scaled. In identifying those, several sequential ionograms should be cross-checked.
- 4. The values of foEs, fbEs and h'Es are scaled from the trace having the highest frequency.

- 5. When Es traces of different types appear simultaneously, respective foEs and h'Es are scaled type by type. In this case, the scaling is made in order of the critical frequency, and if the frequency is same the priority is given to the greater virtual height.
- 6. The auroral and retardation type Es are scaled regardless of the above rules 1-3 even when no overhead reflection is present.

How to distinguish between foEs and fxEs


In scaling Es traces, difficulty often arises in identifying foEs (ordinary wave critical frequency of Es layer). As a matter of fact, the ordinary and extraordinary components of f or £ type Es traces cannot usually be distinguished. In this case, the value of foEs is deduced by subtracting fB/2 (\diangle 0.6 MHz in the middle latitudes) from ftEs (top frequency of the Es layer), assuming that the echo having the highest frequency is the extraordinary component.

As shown in the figure, the distinction of Es layer traces appearing together with the normal E layer traces is not so difficult (in the case of h type and c type).



In most cases, however, the ordinary and extraordinary components of the Es layer traces overlap each other at the same height and so it cannot be simply decided which component gives ftEs.

The interpretation of ftEs is to be made according to the processes shown in Cases 7-16.



R

## foEs 1 h'Es 1

(1) Es layer is not observed ( Daytime )	fmin	16
1 2 3 4 5 6 7 8 9 10 11MHz	foE h'E	270 105
1400	foEs	27EG
	fxEs	
300	h'Es	G
	Es type fbEs	27EG
200	foFl	L(40)
100	h'F	210
	h'F2 foF2	240 66
<u> </u>	fxI	
fmin foE foFl foF2	·	
2 Es layer is not observed ( Daytime )	fmin	17
	foE	S
400	h'E foEs	110 G
300   1   1   1   1   1   1   1   1   1	fxEs	G
300	h'Es	G
	Es type	4
200	fbEs foFl	G 40
	h¹F	245ES
100	h'F2	290
	foF2 fxI	59
fmin foFl foF2	TVT	
(3) Es layer is not observed ( Nighttime )		
	fmin	10EB
	foE h†E	
400	foEs	loee
	fxEs	ئىلدائىد 🗸 سىم
300	h'Es	E
	Es type fbEs	سيستال ل
200	foFl	10EE
100	h'F	240EE
	h'F2	00
<u> </u>	foF2 fxI	33 39X
fmin foF2	A 24 A	
4 Es layer is not observed ( Nighttime )	fmin	13
	foE	
400	h'E foEs	13EB
	fxEs	للتثريد
300	h¹Es	B
	Es type	כונינט ד
200	fbEs foFl	13EB
	h†F	225
100	h'F2	
	foF2	48
fmin foF2	fxI	54X
THE TOP Z		

#### foEs h'Es - 1

Observation: An ionogram to be observed usually in the daytime. Traces in E region (105 km) are of the normal E layer (foE = 2.70 MHz).

Interpretation: The ionosphere is considered to be quite normal. In the E region, only traces of the normal E layer are clearly observed and no trace of Es layer exists. In the lower part of F layer

foEs = (foE)EG h'Es = G

Observation: In the frequency range from 2.6 MHz to 3.4 MHz, traces are not clear owing to the interference. Traces in the E region (110 km) are of the normal E layer.

Interpretation: The value of foE cannot be scaled owing to the interference. But in cases where traces at 110 km are identified as
the normal E layer, and where Es layer is not observed even by
referring to ionograms obtained before and after the time
concerned the letter G is applied for all the scaling parameters
of Es. The letter S is suitable for other cases.

foEs = G

Observation: An ionogram at night. Only F layer traces are observed from 1 MHz (the lowest frequency of ionosonde). No trace exists in the E region.

> foEs = (fmin)EE h'Es = E

Comment: The use of descriptive letter E is limited to the nighttime.

4) Observation: An ionogram at night. fmin (1.3 MHz) is scaled from F layer traces. No trace exists in the E region.

Interpretation: If the ionosonde works normally, the cause of no echo below 1.3 MHz is ascribed to the absorption of ionosphere.

Therefore, descriptive letter B is used.

foEs = (fmin)EB = 13EB

h'Es = B

Comment: When the cause is ascribed to the interference, see Case 5.

## foEs\_2 h'Es\_2

1 2 3 4 5 6 7 8 9 10 11MHz foE h'E foE h'E foEs 16ES fxEs h'Es S Es type foEs 16ES foFl h'F 220ES h'F2 foF2 36 fxI 42X  6 No Es layer is observed owing to absorption fmin 46 foE B h'E B foEs 46EB fxEs h'Es B Es type foEs 46EB foFl B h'F B B foFl B B FOFL B B FOFL B FOF		1		<del></del>
No.	(5)	No Es layer is observed ( Nighttime )	fmin	16ES
Add		1 2 3 4, 5 6 7 8 9 10 11MHz		
1   1   1   1   1   1   1   1   1   1	km 400			3 678C
100   100				TOTO
Stype   FbEs   1GRS	300	+		S
### A A A A A A A A A A A A A A A A A A			Es type	
### A A A A A A A A A A A A A A A A A A	200			16ES
### A A A A A A A A A A A A A A A A A A				೧೧೧೯೮
### ### ### ### ### ### ### ### ### ##	100			ことしたら
Section   Figure				36
6 No Es layer is observed owing to absorption    fmin	-	<del></del>	fxI	Ū2Χ
Solution				
h00	6	No Es layer is observed owing to absorption		
100				
Street   S	400			
Solution				40EB
### Stype   St	300			В
### Page 100   Fee		absorption h'F2	Es type	
Total B   h'F2   255EB   foF2   66   foF2   foF2   66   foF2   foF2   foF2   foF2   foF2   foF3   foF4   foE5   foF4   foE5	200			
h'F2   255EB   foF2   66   fxI				
fmin foF2  ftEs (top frequency of Es layer) is low  fminFx  300  fminFx  300  foEs 12  fxEs h'Es 110  Es type f1  foF1  h'F 220  h'F2  foF2 33  fxI 39X   8 ftEs is higher than fB (gyro frequency)  (Nighttime)  fminFx  foEs 19JA  fxEs 110  Es type f1  foE h'E  foF2 33  fxI 39X	100			
### The content of th				
### The company of th	<b></b>			
Nighttime   fmin   10EE   foE   h'E   foEs   12   fxEs   h'Es   110   Es type   f1   fbEs   12   foF1   h'F   220   h'F2   foF2   33   fxI   39X      State				
# fmin	7	ItEs ( top frequency of Es layer ) is low ( Nighttime )	_	
### ### ##############################		,9		10EE
### Foliable   Foliabl				
Sample   S	400	Fmin Fx		12
Es type f1 fbEs 12 foF1 h'F 220 h'F2 foF2 33 fxI 39X   8 ftEs is higher than fB (gyro frequency) (Nighttime)  fmin 10EE foE h'E foEs 19JA fxEs 25 h'Es 110 Es type f1 fbEs 19 foF1 h'F 210			fxEs	
The content of the	300			
foF1 h'F 220 h'F2 foF2 33 fxI 39X   (Nighttime)  fmin 10EE foE h'E foEs 19JA fxEs 25 h'Es 110 Es type f1 fbEs 19 foF1 h'F 210				
100 h'F 220 h'F2 33 fxI 39X   (Nighttime) fminFx 10EE foEs 19JA fxEs 25 h'Es 110 Es type f1 fbEs 19 foF1 h'F 210 h'F2 foF2 42 fxI 48X	200			15
h'F2   foF2   33   fxI   39X				220
foEs fB  ftEs is higher than fB (gyro frequency) (Nighttime)  fmin 10EE foE h'E foEs 19JA fxEs 25 h'Es 110 Es type f1 fbEs 19 foF1 h'F 210 h'F2 foF2 42 fxI 48X	T00 -			
### Tobs				i
( Nighttime ) fmin 10EE  foE  h'E  foEs 19JA  fxEs 25  h'Es 110  Es type f1  fbEs 19  foF1  h'F 210  h'F2  foF2 42  fxI 48X	foEs		fxI	39X
foE h'E foEs 19JA fxEs 25 h'Es 110 Es type f1 fbEs 19 foF1 h'F 210 h'F2 foF2 42 fxI 48X	8	ftEs is higher than fB (gyro frequency) (Nighttime)	fmin	10EE
foEs 19JA fxEs 25 h'Es 110 Es type f1 fbEs 19 foF1 h'F 210 h'F2 foF2 42 fxI 48X			foE	- <del></del>
fminFx fxEs 25 h'Es 110 Es type fl fbEs 19 foFl h'F 210 h'F2 foF2 42 fxI 48X	)   			
h'Es 110 Es type fl fbEs 19 foFl h'F 210 h'F2 foF2 42 fxI 48X	400			
Es type fl fbEs 19 foFl h'F 210 h'F2 foF2 42 fxI 48X	300	<del>                                     </del>		,
fbEs 19 foF1 h'F 210 h'F2 foF2 fxI 48X	500 .			
100 h'F 210 h'F2 foF2 42 fxI 48X	200 -		fbEs	
100 h'F2 foF2 42 fxI 48X				0.7.0
foF2 42 fxI 48X	100			5T0
	TOO .			42
	fВ	JfbEs    fxEs		

5 Observation: An ionogram at night. Traces below 1.6 MHz are not clear owing to severe interference.

Interpretation: MF broadcast interference as shown in the figure is recorded usually on ionograms obtained at midlatitude stations during nighttime hours. This type of ionogram is frequently seen during dark hours except those from midnight to dawn when the BC stations stop their services. The descriptive letter expressing the cause of lack of traces should be used in the same way as fmin. h'Es would usually be only the letter.

foEs = (fmin)ES = 16ES h'Es = S

Comment: If the cause is the trouble with the ionosonde, C is used instead of the letter S.

6 Observation: In the frequency range below 4.6 MHz, no traces are observed.

Interpretation: Malfunction, interference and absorption can be considered as the cause of disappearance of traces. This figure refers to the absorption which occurs mainly in the daytime and sometimes lasts for several hours. The absorption condition can be easily distinguished from others, since it makes weak both the interference and the echoes. Es traces are interpreted to be below fmin.

foEs = (fmin)EB = 46EB h'Es = B

Comment: In the case where the traces are not observed at all owing to the absorption, all the parameters are expressed by the symbol B.

7 Observation: An ionogram at night. The top frequency of Es layer (ftEs) is 1.2 MHz.

Interpretation: In the lower part of F layer traces the extraordinary component (fminFx) is also observed. Since f type Es traces extending up to 1.2 MHz are observed from the lowest frequency of ionosonde, there would be almost no absorption. When the value of ftEs is small, foEs should be determined in comparison with fB. In this case, since ftEs is smaller than fB, ftEs = foEs.

foEs = 12 h'Es = 110

Comment: fB: gyro-frequency (the frequency at which the electrons gyrate around the geomagnetic field). The value of fB varies depending on the location of the station and the ionospheric height concerned. In middle latitudes, it is about 1.2 MHz.

Observation: An ionogram at night. The top frequency of f type Es (ftEs) is 2.5 MHz.

Interpretation: Since Es layer traces are observed from the lowest


frequency of ionosonde, the absorption should be small. In

this case, since ftEs is much larger than fB, ftEs = fxEs.

foEs = (fxEs - fB/2)JA = 19JA

h'Es = 110

### foës h'Es - 3



9 Observation: The c type Es is observed. ftEs = 7.2 MHz. The lower part of Fl traces is blanketed by the Es layer.

Interpretation: Since the ordinary and extraordinary components of Es trace overlap each other near ftEs, they cannot be distinguished. foEs should be identified in comparison with the lowest frequency of the extraordinary component (fminFx) of a higher trace. In this case, ftEs is larger than fminFx and so ftEs is fxEs.

foEs = (fxEs - fB/2)JA = 66JAh'Es = 115

Observation: The  $\ell$  type Es is observed up to the 3rd order reflection. ftEs = 5.6 MHz. This  $\ell$  type Es is blanketing the lower part of normal E layer.

Interpretation: It is not clear whether ftEs of  $\ell$  type Es is ordinary or extraordinary component. Being based on the same principle as in Case 9, the lowest frequency of E layer trace extraordinary component (fminEx) is compared with ftEs. Since ftEs is much larger than fminEx and fminFx, ftEs should be identified as fxEs.

foEs = (fxEs - fB/2)JA = 50JAh'Es = 100

(11) Observation: ftEs of the c type Es observed is 4.3 MHz.

Interpretation: Ordinary and extraordinary components of Es layer cannot be distinguished. It is to be interpreted in the same way as in Case 9. Since ftEs is equal to fminFx, ftEs = fxEs.

foEs = (fxEs - fB/2)JA = 37JAh'Es = 125

Observation: ftEs of & type Es is 3.7 MHz and 2nd order reflection is observed. Traces of Fl and F2 layers are normally observed.


Interpretation: The interpretation given in Case 11 is also valid for this case. Since ftEs of & type Es is equal to fminEx, ftEs = fxEs.

In this figure, since foEs is smaller than foE, the descriptive letter G is applied.

foEs = (fxEs - fB/2)JG = 31JG

h'Es = 105

# foEs \_ 4



0bservation: The h type Es trace is tangential to the E layer trace at foE. ftEs = 3.9 MHz.

Interpretation: It is to be interpreted in the same way as in Cases 9 and 11. When ftEs and fminFx are compared, fminFx is larger than ftEs and the separation between them exceeds fB/2 (about 0.6 MHz). Hence, ftEs = foEs.

foEs = 39

h'Es = 130

Observation: The & type Es ftEs of which is equal to 3.0 MHz blankets the lower part of normal E layer trace.

Interpretation: foEs is determined by applying the interpretation of Case 13 to E region trace as follows: Since ftEs of  $\ell$  type Es is smaller than the value (fminEx - fB/2), ftEs = foEs. Since this foEs is clearly smaller than foE, it is marked with the descriptive letter G.

foEs = 30G

h'Es = 100

Comment: When ftEs falls in a range between fminEx and (fminEx - fB/2), ftEs should be interpreted as fxEs. The descriptive letter G is necessary.

foEs = (ftEs - fB/2)JG = xxxJG

Observation: The & type Es layer trace extends up to 8.0 MHz and even the 3rd order reflection is observed. F layer trace is completely blanketed.

Interpretation: In the case of total blanketing, fminF cannot be obtained from the procedures as mentioned in Cases 7 - 14. It is interpreted that the F layer extraordinary component is blanketed by Es layer extraordinary component. Generally speaking, if both the absorption condition and the F layer are normal, ftEs = fxEs.

foEs = (fxEs - fB/2)JA = 74JAh'Es = 105

Comment: The above interpretation cannot be applied to the case where the F layer electron density has been unusually reduced (foF2 is low) owing to the geomagnetic storm, for example.

Observation: F layer trace below 5.4 MHz is blanketed by & type Es. ftEs = 6.4 MHz.

Interpretation : The ordinary and extraordinary components overlap each
 other in the lower part of F layer trace. Therefore, it is
 impossible to identify the component of ftEs from fminFx.
 In this case it is necessary to apply the following rules to
 the Es trace itself:

1. Absorption is small (fmin is low). ---- ftEs = fxEs

2. The ftEs is nearly equal to foEs (it is interpreted that the extraordinary component of Es layer trace is absorbed).
----- ftEs = foEs

3. The ftEs is much higher than foE (it is considered that extraordianry component exists naturally). ---- ftEs = fxEs In Case 16, either 1 or 3 is applied.

foEs = (fxEs - fB/2)JA = 58JA

h'Es = 110

### foEs h'Es 5

<del></del>					······································	·····		<u> </u>		······································				
17	Ne	ar ft. nnot	Es, or be dis	dinary tingui	/ and ished	extrac (Night	ordina ctime)	ry com	ipone	nts		1	fmin	11
	1 2		3 4	, r	5 6	***************************************		_	9 :	10	111	MHz	foE	
km	_		Ĩ İ			' I	•	, 	, 	ĺ	J. J. I.	1112	h'E	0071
400 -			1		•								foEs fxEs	33JA 39
300 -													h'Es	110
300			<i>/</i> .::	:::·									Es type	fl
200 -	<u> </u>												fbEs	23
										-			foFl h'F	220EA
100 -					.,								h'F2	ZZOWA
		A	A										foF2	40F
	Min f	Ph.Tr.o	fxl	20									fxI	52
					n s	7 0750	20 0354	raord	lina	rits i	trac	es	<del> </del>	
(18)	are s	seen	to be	conr	necte	i aye	T GY	) I CLU (		J			fmin	17
													foE	300
400 -													h'E foEs	110 34
						}	)						fxEs	34 40
300 -			ļ			_/_	/						h'Es	120
													Es type	cl
200 -				D. Control									fbEs foFl	30EG L(47)
													h'F	220
100 -	-												h'F2	265
			l a			•							foF2	68
-	fmi	<u> </u>	7 4	7-				<u>L.</u>	L				fxI	
					100+10			up to 1	مام دام	~ 30	***************************************			
(19)	f	reque	a orae ncy th	an the	e lst	order	refle	ection	nigin iN)	er ghtt	ime)		fmin	18
													foE	10
1.00													h'E	
400 -													foEs	52
200 -	3E	5											fxEs	105
300 -													h'Es Es type	105 f3
200 ·	2Es												fbEs	52AA
													foFl	,
100 -													h 'F	Α
													h¹F2	٨
	4				4								foF2 fxI	A A
-	fmi	.n		f	`oEs									
20		Obli	que r	eflec	tion	trac	e is	obser	ved				fmin	16
						1	,		<u> </u>		T		foE	Α
1,00							1	_				- 1	h'E	100
400						1	/			1		$\neg \neg$	foEs	68JA
200		3Es											fxEs h'Es	74 100
300 -			- William										Es type	c3
200 -		2Es	***************************************										fbEs	49
200							ot	lique	tr	ace			foFl	A
100				Decouration v	THE PERSON NAMED IN COLUMN								h'F h'F2	A 250UA
1.00										de la constante de la constant			foF2	67
	<u> </u>			A			<b>A</b>		<u> </u>				fxI	•
	fmin			fbl	m		fxEs							

0bservation: The spreading of echoes are seen in F layer trace. The f type Es is observed. ftEs = 3.9 MHz.

Interpretation : The fminFx cannot be determined from F layer traces in
 this figure. In addition, since fmin is 1.1 MHz, it is
 considered that there is almost no absorption. Applying
Rule 1 in Interpretation of Case 16, ftEs = fxEs.

foEs = (fxEs - fB/2)JA = 33JA

h'Es = 110

Observation: The ordinary and extraordinary components of c type Es are observed separately.

foEs = 3.4 MHz, fxEs = 4.0 MHz.

Interpretation: This is a very common ionogram. As shown in the figure, discontinuity of trace at foEs which is deduced from fxEs is usually found by careful examination of trace.

foEs = 34

h'Es = 120

Comment: Attention should be paid to the case where the 2nd order reflection of Es layer sometimes overlap the F layer trace (see Case 11 of h'F).

Observation: Multiple echoes of f type Es are recorded. The 2nd order reflection extending up to 6.6 MHz shows higher top frequency than that of the 1st order reflection.

Interpretation: It is found in ordinary ionograms that as the number of reflections increases the trace becomes weaker lowering the top frequency. Therefore, this ionogram seems to be affected by oblique reflections, although heights are consistent with overhead reflections.

foEs = 52

h'Es = 105

Observation: The c type Es is seen up to the 3rd order reflection.

fxEs = 7.4 MHz. Another trace is observed from 5.5 MHz to

10.6 MHz at a virtual height of 130 km.


Interpretation: Multiple echoes of c type Es are regarded as vertically reflected ones from relative difference of the virtual height. Since the trace near 130 km which is observed neither before nor after the time of this ionogram shows slight spreading, this should be interpreted as an oblique reflection.

Therefore, no scaling is necessary.

foEs = (fxEs - fB/2)JA = 68JA

h'Es = 100

### foEs h'Es - 6



(21)

Observation: Top frequency of c type Es exceeds the maximum frequency (see Comment) of ionosonde. F layer traces are entirely blanketed by Es layer (total blanketing).

Interpretation: In summertime (May-July in the Northern Hemisphere) when
Es layer develops, this type of record is sometimes seen for
more than one hour. In this case foEs is expressed referring
to the upper frequency limit of ionosonde with the qualifying
letter D (larger) and the descriptive letter D (exceeding the
limit).

foEs = (upper frequency limit of ionosonde)DD = 200DD h'Es = 110

(22)

Observation: The & type Es (h'Es = 100 km) blankets the lower part of normal E layer, while c type Es (h'Es = 135 km) blankets the lower part of Fl layer traces.

Interpretation: In this ionogram are observed two types of Es each of which has its own critical frequency. But the higher foEs should be scaled in the table as representative.

foEs = 50

h'Es = 135

Since foEs of  $\ell$  type Es is lower than foE, the foEs is expressed with the descriptive letter G. foEs = 34G

(23)

Observation : The h and  $\ell$  types Es are recorded at the height of 155 km and 100 km respectively having the 2nd order reflections.

Interpretation: This type of ionogram is often seen in the season when the Es activity is large. The h type Es is likely to change into c type and then  $\ell$  type, lowering the virtual height. Since the top frequency of  $\ell$  type Es is the highest one, it is regarded as a representative value.

foEs = 66JA

h'Es = 100

For h type Es, foEs = 51, h'Es = 155 and fbEs = 46.

(24)

Observation: Both components of h type Es are observed in clear separation, although horizontal parts of trace are missing.

Interpretation: In this case, when the Es trace does not become horizontal, the virtual height at foEs is qualified by letter U or E as required by the accuracy rules, and described by the letter G.

foEs = 36

h'Es = 150EG

### Classification of Es types

### @ Es types :

Es traces are classified into one of 11 types. There are  $f, \ell$ , c, h, q, r, a, s, d, n and k. Types to be observed at a station are not so many. The  $f, \ell$ , c and h types are observed in the middle latitude, while a and r types are normally but not exclusively observed in the high latitude.

### @ Classification :

- 1. All Es traces recorded in the ionogram should be classified with the identification of types.
- 2. The rules state that foEs, h'Es and fbEs should not be scaled from weak or oblique reflections. However, all Es types should be included in the table (e.g. d type Es or s type Es).
- 3. When the gain of ionosonde is low or when the type cannot be identified because of complexity of traces, the ionograms of high gain observation or the observation made within one hour should be referred to.


#### @ How to indicate Es types and multiple reflections :

- 1. The lower case letters should be used for Es types to be indicated in the scaling table.
- 2. When several kinds of Es types are seen in an ionogram, the type of trace from which the representative value of foEs is scaled should be indicated first. The types of the rest of Es traces are indicated in sequence of descending order of multiples.
- 3. In recording the types in the scaling table, they should be followed by the number (not exceeding 9) of multiple reflections (For details, see I.H. p. 179, Table 8.1).

#### [Example]

In the figure, h and  $\ell$  types are seen up to  $\ell$  and 3 reflections respectively. Es type is expressed as follows:

h4l3



In the case of no multiple reflections, omission of the number of reflections is allowed excepting the tabulation for computer input.

For example: h4l3

4. Each column of the scaling table has a space for 5 letters. This means that there is no space for the number of reflections of 3rd type of Es (e.g.  $h3c2\ell$ ). For details, see I.H. p.179, Table 8.1.


# type of Es -1

1 Es type f, flat	fmin	10EE
1 2 3 4 5 6 7 8 9 10 11MHz	foE h'E	(0.74
300 3Es	foEs fxEs h'Es	62JA 68 100
200 2Es Es-f	Es type fbEs foFl	f3 48
100	h'F h'F2	250EA
fmin fbEs fxEs	foF2 fxI	65 71X
(2) Es type L, low	fmin	14
400	foE h'E foEs	315 115 42JA
300	fxEs h'Es Es type	48 105 &1
Es-L	fbEs foFl	22G
00	h'F h'F2 foF2	270 67
fmin fbEs foE fxEs	fxI	
3 Es type c, cusp	fmin	15
.00	foE h'E foEs	300 105 44
300	fxEs h'Es	51 110
Es-c	Es type fbEs foFl	cl 30EG L(46)
00	h'F h'F2	245 310
fmin foE foEs fxEs	foF2 fxI	79
4) Es type h, high	0.1	-,
	fmin	15
	foE h'E foEs	320 110 46
00 00	foE h'E foEs fxEs h'Es Es type	320 110 46 52 155 hl
00 00 Es-h	foE h'E foEs fxEs h'Es Es type fbEs foF1	320 110 46 52 155 h1 44 A
00 00	foE h'E foEs fxEs h'Es Es type fbEs	320 110 46 52 155 hl 44

### type of Es-1


f (flat) type is a type whose virtual height does not change as the frequency increases. This type is observed at any latitude. This classification is applied exclusively in the nighttime. The flat Es layer trace which is observed in the daytime should be classified into \(\ell\), c or h types, depending on its virtual height relative to that of the E layer.

(2) & (low)type is a flat Es trace appearing at a height equal to or less than the minimum virtual height of the normal E layer. Therefore, this classification is applied mainly to Es in the daytime.




When the particle E layer is observed in the nighttime, a flat Es layer is tabulated as the  $\ell$  type, as in the case of daytime.

c (cusp) type is an Es trace which shows a comparatively symmetrical cusp at a frequency at or below foE. A part or the whole of the cusp is sometimes missing. This type of Es is observed up to higher frequencies, being connected to the thick E layer trace, and hence can be applied only in the daytime, or nighttime to particle E.




In this figure, the trace in higher frequencies above the cusp is c type Es which masks dotted part of the normal E trace.

h (high) type is an Es trace showing a discontinuity in height with the normal E layer trace at or above foE. The cusp is not symmetrical, the height of the low frequency part of the Es trace being clearly higher than that of the high frequency part of the thick E layer trace. It is applied only in the daytime, or nighttime particle E.



In the figure, the Es trace having a cusp made by the intermediate stratification (E2 layer) is also treated as the h type.

## type of Es -2




## type of Es-2

(5)

q (equatorial) type is an Es trace which is commonly found during daytime in the vicinity of the magnetic dip equator, showing diffuse and transparent characteristics. The lower edge of the trace is relatively well-defined. This type of Es is frequently observed in coexistence with other types of Es. Another important feature is that foEs greatly exceeds fbEs for an Es-q layer.

(6)

r (retardation) type is an obliquely reflected particle E trace showing an increase in virtual height near the top frequency similar in shape to the group retardation of a normal E layer. The trace blankets a part or all of normal E and F layer traces.



In the figure in this column, if b is larger than a, this Es layer should be scaled as r type, while if b is nearly equal to a, the Es would be the particle E layer.

 $\overline{7}$ 

a (auroral) type is usually observed only in high latitudes but can be observed at mid-latitudes in association with auroral activity. This type is applied to various types of spread Es traces. The spreading ranges over several hundred kilometers in virtual height. Echo patterns show flat or slowly rising lower edge having rapidly changing stratified structure. The width of the trace is greatest usually at frequencies below ftEs and sometimes at frequencies near fminF. The Es pattern usually alters rapidly in time.

(8)

s (slant) type is a diffuse trace the virtual height of which increases steadily with frequency, emerging usually from such a point of underlying horizontal traces as the foE, fxE, foEs, fxEs, or an intermediate point in the Es trace. The s type must not be applied to the horizontal part, but should be applied to just the slant part of trace. This type is mainly observed in high latitudes, the starting point of slant part varying with the magnetic latitude.

The s type trace must not be used to determine foEs, fbEs or h'Es, but should be included in the type of Es table.

# type of Es - 3

9 Es type d, Partial reflection from absorbing layer	fmin	67
1 2 3 4 5 6 7 . 8 9 10 13MHz	foE h'E	B B
400 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	foEs fxEs	67EB
300	h'Es	В
200	Es type fbEs	dl 67EB
Es-d	foFl h'F	B B
	h'F2 foF2	280́ЕВ 75
fmin foF2	fxI	17
10 Es type k, particle E	fmin	14
1805 (char	foE	250K
400	h'E foEs	150K 25K
300	fxEs h'Es	31K 150K
Es-k	Es type fbEs	kl 25K
200	foFl h'F	
100	h'F2	280
<u> </u>	foF2 fxI	65F 74
fmin foE foF2		
	fmin	
400	foE h'E	
	foEs fxEs	
300	h'Es Es type	
200	fbEs	:
100	foFl h'F	
100	h'F2 foF2	
	fxI	
0	fmin	
	foE h'E	
400	foEs fxEs	
300	h'Es	
200	Es type fbEs	
200	foF1 h'F	
100	h'F2	
	foF2 fxI	
	·····	

# type of Es-3

9	d (D region) type is a weak diffuse trace which appears normally at heights below 95 km, being associated with high absorption (large fmin). Since this is not strictly an Es trace, it should not be used for determining fmin, foEs and h'Es.  This type has no blanketing capability but the associated absorption may prevent reflections from higher layers. In practice, it is often observed at heights near 80 km.
10	The letter K means the presence of particle E layer. The particle E layer is a thick layer which is sometimes seen at greater heights up to about 170 km in the nighttime, having much higher critical frequency than the normal E layer. It is often observed with type r or type a trace in high latitudes. As for the examples of particle E layer, refer to Cases 17-20 of foE.
<u> </u>	
0	

### @ Definition :

fbEs is the blanketing frequency of the Es layer, namely the frequency at which the Es layer first allows reflections from upper layers.

In other words, it corresponds to the frequency from which the reflections from a higher layer than the Es layer begin to appear. Thus, fbEs is a measure expressing the transparency of the Es layer.

fbEs is always decided by the lowest frequency of the ordinary component of a higher layer observed through the Es layer.

### @ Scaling accuracy :

fbEs is scaled at the accuracy of 0.1 MHz (e.g. 2.6 MHz).

#### @ Indication of scaled value :

fbEs is expressed by the numerical value with or without letters, or by only a letter.

(Examples)

G --- Descriptive letter to be used when no numerical value of fbEs is given in the daytime.

46UY --- U is the qualifying letter, Y is the descriptive letter.

### @ Notices for scaling :

- 1. Since fbEs is affected by the sensitivity of the ionosonde, it should always be scaled from the ionogram obtained with the normal gain.
- 2. All the columns of fbEs in the table should be filled in with any numerical values and/or letters.
- 3. fbEs should always be scaled from the ordinary component.
- 4. Except in special cases, the value of fbEs must be equal to or smaller than that of foEs (for a special case, see Case 11).

- 5. Since fbEs varies with time, it is desirable to obtain as many numerical values as possible so that the number of counts for calculating the monthly median be increased.
- fbEs should be an indication of blanketing effect of the Es trace whose foEs is tabulated. If the several types of Es layer are recorded on an ionogram, the tabulated value of fbEs is always given by trace with highest value of foEs (R.H. p.121, Fig. 4.19).
- 7. In scaling fbEs when the complete blanketing occurs, refer to rules (a) and (b) on p.68 and Figs. 3.1 and 3.2 on p.69 in R.H.

#### How to decide fbEs

In scaling fbEs, it is recommended to examine the ionogram according to the following steps.

- 1. First of all, it should be examined whether or not the Es trace is observed on the ionogram. If it is not go to step 2. If it is observed, go to step 3 and the succeeding ones.
- 2. The case where the Es layer is not observed.
  - (1) The ionogram is normal.

The letter G is appropriate for the daytime, while the letter E for the nighttime. For example:

fbEs = (foE)EG for the daytime,

fbEs = (fmin)EE or

(fmin)ES for the nighttime.

- (2) The ionogram is affected more or less by interference, instrumental fault or absorption.
  - a. No traces at all.

The same letter as used for other parameters is also applied to fbEs (e.g. B,C).

b. Traces are partly observed.

For example: fbEs = (fmin)ES.

3. A case where the Es layer is observed but does not seem to affect upper layers.

This case is envisaged when the lowest frequency of the Es layer, fminEs, is at or above that of upper layers.

The letter G is appropriate for the daytime, while the letter E for the nighttime. For example:

fbEs = (foE)EG for the daytime,

fbEs = (fmin)EE or

(fmin)ES for the nighttime.

- 4. A case where the Es layer observed seems to affect upper layers.
  - (1) Only the Es trace is observed on the ionogram.
    - a. It entirely blankets upper layers (see Item 7 on p.53).

For ftEs = foEs, fbEs = (foEs)AA

For ftEs = fxEs, fbEs = (fxEs - fB/2)AA

b. Both Es traces of the first and second order reflections exceed the upper frequency limit of ionosonde.

fbEs = (upper frequency limit of ionosonde)AA

c. One of Es traces of the first and second order reflections exceed the upper frequency limit of ionosonde.

fbEs = ftEs of the other order reflection

d. The F trace is obscured due to the interference and other causes but seems to be foF2 > foEs.

fbEs = (foEs)ES. S: Interference

- (2) ftEs of the Es trace is compared with the lowest frequency of upper layers (fminF or fminE).
  - a. The ordinary and extraordinary components of Es trace are clearly separated.

For foEs  $\geq$  fminF (or fminE), fbEs = fminF (or fminE).

For foEs < fminF (or fminE), fbEs = (foEs)UY or (foEs)ES

b. ftEs is regarded as foEs.

For foEs ≥ fminF (or fminE), fbEs = fminF (or fminE).

For foEs < fminF (or fminE), fbEs = (foEs)UY,(foEs)UR or (foEs)ES.

c. ftEs is regarded as fxEs.

For (ftEs - fB/2)  $\stackrel{>}{=}$  fminF (or fminE), fbEs = fminF (or fminE). For (ftEs - fB/2) < fminF (or fminE), fbEs = (foEs)UY.

[Note]

Concerning the interpretation that ftEs is either foEs or fxEs, see Cases 7 - 16 of foEs.

(3) foEs of  $\ell$  type Es is smaller than foE.

fbEs = (fminE)G

5. When two or three types of Es are recorded, fbEs of respective type should be tabulated in the column of fbEs according to the steps 3 to 4. Priority is given to the fbEs corresponding to Es trace having the highest foEs. It is the representative value of fbEs for the ionogram.

# fbEs - 1

1 No Es trace is observed (Daytime)	fmin	15
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	foE h'E foEs	290 110 <b>29E</b> 0
300	fxEs h'Es Es type	G
200	fbEs foFl	29E0 44
	h'F h'F2 foF2	230 275 69
fmin foE foF1 foF2	fxI	
2 Presence of Es trace is not identified (Daytime)	fmin foE	20R 200U
00	h'E foEs	B 20E1
00   nt	fxEs h'Es Es type	В
100 ference	fbEs foFl	20E
00   8	h'F h'F2	240
fmin foF2	foF2 fxI	51
3 No Es trace is observed (Nighttime)	fmin	16E
	foE h'E	100
	foEs fxEs	16E
00	h'Es Es type	S
	fbEs foFl h'F	16E
.00	h'F2 foF2	250 55
fmin foF2	fxI	61X
4 No Es trace is observed (Nighttime)	fmin foE	loe
00	h'E foEs fxEs	10E
00	h'Es Es type	E
00	fbEs foFl	10E
00	h'F h'F2	230E
fmin foF2	foF2 fxI	29 35X
fmin foF2	1	

### fbEs - 1

1

Observation : The ionogram in quiet conditions. The E region trace

is of the normal E layer. foE = 2.90 MHz

Interpretation: In case where only the normal E layer is observed in

the E region (no Es trace is observed), all the parameters concerning Es are expressed with the

letter G.

fbEs = (foE)EG

(2)

Observation : In the range below 1.6 MHz the trace is not clear due to

the interference. The F layer trace is observed from 2.0

MHz but both the normal E and Es traces cannot be identified.

Interpretation: There is no interference between 1.6 and 2.0 MHz.

foE can be deduced to be 200UB from the retardation of

the lowest part of the F trace.

foEs = 20EB.

Therefore, fbEs = 20EB

(3)

Observation : Only the F trace is observed. No trace is observed in

the frequency range below 1.6 MHz due to the interference.

Interpretation : This kind of ionogram is found often in the nighttime

when the Es activity is low. The interference by MF
Broadcasting is very common in the nighttime at midlatitude sounding stations. Since the existence of Es
cannot be identified below fmin due to the interference,

the letter S is to be used for Es parameters.

fbEs = (fmin)ES = 16ES

Comment: In the case of no traces due to some instrumental failure,

the letter C is used instead of S.

(4)

Observation: Nighttime ionogram. The F trace is observed from the

lower frequency end of ionosonde. fmin = 10EE

Interpretation: There is no Es trace in the frequency range above

1.0 MHz. In this case the Es trace is considered to

exist below the lowest frequency limit of the ionosonde.

fbEs = (10)EE

Comment: If fmin is higher than the


lowest frequency as shown in the

figure,

fbEs = (fmin)EB.



### fbEs-2



### fbEs - 2

5

Observation: foE is 3.90 MHz and c type Es is observed. The retardation is seen at the lower frequency end of the F trace. fmin is a little higher than usual.

fbEs = (foE)EG

**(6)** 

Observation: Nighttime ionogram. The f type Es is seen at the height of 100 km. The F trace is observed from the lowest frequency of ionosonde.

fmin ≤ 1.0 MHz.

Interpretation: fbEs should be decided from the comparison of fminEs

(the minimum frequency of Es trace) with fminF (the minimum frequency of F trace). If both are equal or fminEs
is larger than fminF, it is interpreted that there is no
influence of the Es layer.

 $\overline{7}$ 

Observation: Only the F trace is observed from 4.9 MHz. fmin = 4.9 MHz.

Interpretation: It is necessary to confirm by referring to the sequence of ionograms the cause of the disappearance of the trace. In this case, the cause would be the absorption (B) due to SID (Sudden Ionospheric Disturbance). fbEs is expressed by marking the numerical value of fmin with the qualifying letter E (smaller) and the descriptive letter B (absorption).

fbEs = 49EB

Comment When the cause is other than absorption, the descriptive letter is changed to conform (e.g. C for non-ionospheric reason).

(8)

Observation: Both components of c type Es are observed in the vicinity of 120 km, together with the ordinary component of the second order reflection.


foEs = 5.3 fxEs = 6.0 MHz.

The value of foFl is around 5.8 MHz.

Interpretation: fminF (5 MHz) is lower than foEs. Therefore, it is interpreted that the Fl trace below 5 MHz is totally blanketed by c type Es.

fbEs = 50

## fbEs-3



### fbEs - 3

Observation: The f type Es extending up to 4.9 MHz blankets the F trace below 2.6 MHz. A mixed reflection is recorded.

Interpretation: No particular consideration is needed, if ftEs (the top frequency of Es layer) and fminF are separated by more than half of the gyro frequency (fB/2 = 0.6 MHz), as shown in this figure.

fbEs = 26

If not, foEs and fminF should be compared to determine fbEs, after confirming whether ftEs = foEs or ftEs = fxEs.

Comment: Detailed explanation related to this Case is given at Step 4(2) in "How to decide fbEs" on page 55. As for the mixed reflection, see Appendix 1 on p.118 of this manual.

Observation: The f type Es extends up to 5.7 MHz, showing also the second order reflection. The F trace below 5.3 MHz is blanketed.

Interpretation: This Case is similar to Case 9. But fminF in this ionogram is separated from ftEs by only 0.3 MHz.

If ftEs = foEs, fbEs = 53.

If ftEs = fxEs, foEs = (fxEs - fB/2) = 51JA. Therefore, foEs < fminF. According to Step 4(2)c on p. 55 of this manual, fbEs = (fxEs - fB/2)UY = 51UY.

Observation: The ordinary component of h type Es is observed at about 150 km. foEs = 3.5 MHz. A gap of 0.2 MHz is seen between foEs and fminF.

Interpretation: Basically fbEs cannot be greater than foEs. Since it is inferred that the F trace near fminF is influenced by the oblique reflection, the letters U (doubtful) and Y (F layer tilt) are used.

fbEs = (foEs)UY = 35UY

Comment: When the inference is not certain, indication by only the letter is preferable.

0bservation: Nighttime ionogram. The trace between 3.2 and 4.0 MHz is not clear owing to the interference.

Interpretation: fbEs is considered to be between 3.2 and 4.0 MHz.


fbEs is expressed by marking the numerical value of ftEs

with the letters D (greater) and S (interference).

fbEs = (ftEs)DS = 32DS

Comment: Since the ambiguity of fbEs increases as the interference gap in frequency becomes large, it is rather desirable to express fbEs only by the descriptive letter S.

### fbEs-4



13)

Observation: The f type Es is observed both the components of which are clearly separated. foEs (2.8 MHz) is lower than foE (3.15 MHz). No Fl layer is observed.

Interpretation: This & type Es blankets the lower part of the normal E layer. In order to express that foEs is less than foE, both the numerical values of foEs and fbEs are accompanied by the letter G.

fbEs = (fbEs)G = 22G

Comment: In the case where fmin of  $\ell$  type Es is equal to or larger than fminE, it is interpreted that there is no influence of the Es layer. Thus, fbEs = G

(14)

Observation: The c type Es traces are observed up to the third order reflection. foEs = 9.7 MHz and fxEs = 10.4 MHz. The F layer trace is blanketed by the c type Es (Total blanketing).

Interpretation: The total blanketing gives us no information of fbEs.

Assume that foF2 be approximately 6.5 MHz being inferred from the sequence of ionograms. Since foF2 (6.5 MHz) is much smaller than foEs (9.7 MHz), fbEs is scaled with the qualifying letter A (smaller than) and the descriptive letter A (affected by Es) as follows:

fbEs = (foEs)AA = 97AA

Comment: In the case where ftEs is close to the inferred foF2 and it is not clear whether ftEs is foEs or fxEs, foEs has to be decided firstly and then Case 15 is referred to.

(15)

Observation: The c type Es extends up to 7.0 MHz. The lower part of the F trace is blanketed by this Es layer. Severe interference masks all traces from 7.0 MHz to 8.3 MHz.

Interpretation: In this ionogram it is not clear whether ftEs is foEs or fxEs. If foF2 inferred from the sequence of ionograms is considered to be in the band of interference,

fbEs = foEs = (ftEs)DS = 70DS



Observation: The f type Es traces are observed up to the fourth order reflection. ftEs = 6.9 MHz. The F trace is of the second order reflection.

Interpretation: The first order reflection from the F layer is not recorded owing to the blanketing by the Es layer (dotted lines). Since fbEs should be scaled from the second order reflection, the recorded F trace is ignored.

fbEs = (top frequency of 2Es)AA = 54AA

# fbEs - 5

r ———			
(17)	Only the extraordinary component of Es trace is observed	fmin	17ES
	1 2 3 4 5 6 7 8 9 10 11MHz	foE	S
km		h'E	S
400 -		foEs	17JS
200	inte	fxEs h'Es	23 S
300 -		Es type	hl
	er	fbEs	17ES
200 -	Es-h	foFl	± 1 ± 5
	Es-11	h'F	235
100 -		h'F2	
		foF2	36
	fmin fxEs foF2	fxI	
	Overlapping of the F layer and Es layer (second order		
(18)	reflection) traces makes difficult the scaling of fbEs	fmin	14
		foE	
400 -	4Es	h'E	*O
1400 -		foEs	28JA
300 -	3Es	fxEs h'Es	34 100
300 -		Es type	f4
	2Es	fbEs	25UA
200 -	C. Li Q	foFl	
		h † F	200A
100 -		h'F2	
		foF2	71
f	Timin fbEs fxEs	fxI	77X
<b>—</b> —			
(19)	Two types of Es are observed		
		fmin foE	15 350
		h † E	115A
400 -		foEs	48
		fxEs	54
300 -		h'Es	140
	Es-h	Es type	hll1
200 -		fbEs	45
		foFl h'F	45UA
100 -	Appendix Marian	n'r h'F2	A 305
		foF2	61
<del>J</del>	min fbEs foEs foEs	fxI	<del></del>
(20)	Two types of Es are observed (Mutual blanketing between Es layers)	fmin	16
		foE	310UA
1		h'E	A
400 -		foEs	56
		fxEs	62
300 -	3Es	h'Es Es type	115 cll3
	200	fbEs	34
200 -	2Es Es-c	foFl	L(41)
	Es-L F	h'F	240EA
100 -	The state of the s	h'F2	270
		foF2	614
<b> </b>	fmin fbEs foEs foEs	fxI	
	THE TOPS TOES TOPS		

(17)

Observation : No trace is seen below 1.7 MHz owing to the interference.

The trace in the E region seems to be the extraordinary component of h type Es. fxEs = 2.3 MHz.

There is a weak retardation in the low frequency part of the

Interpretation: This kind of ionogram appears frequently around sunrise or sunset. Traces of the normal E layer and of the ordinary component of h type Es (dotted lines) are masked by the interference. Same interpretation as Case 3 is appropriate.

fbEs = (fmin)ES = 17ES

(18)

Observation: The f type Es traces are recorded up to the fourth order reflection. foEs = 2.8 MHz. Lower part of F trace is apparently merged into the Es layer second order reflection at the height of 200 km.

Interpretation: This kind of ionogram appears frequently when the Es activity is high. In this Case, the reference to the second order reflection of the F layer would be helpful in identifying fbEs, as shown in the figure. Since, however, the numerical value is doubtful, the qualifying letter U is used.

fbEs = 25UA

Comment: Even in the case where the second order reflection cannot be utilized, the approximate values of fbEs can be decided often by referring to the width of each trace and the sequence of ionograms.

19

Observation: foEs of h type Es at 140 km is 4.8 MHz, while foEs of  $\pounds$  type Es is 3.0 MHz. The Fl layer is blanketed by the h type Es.

Interpretation: fbEs is scaled for each type of Es. Since fbEs is the blanketing frequency for the layer seen through the Es layer, two values of fbEs corresponding to h and & type Es traces must be obtained independently from the F and E layer traces respectively. Larger value of fbEs for h type Es is tabulated first as the representative value.

fbEs = 45 (h type)

fbEs = 23G (& type; the letter G is attached because foEs < foE).

(20)

Observation : Both c type Es (foEs =  $5.6 \, \text{MHz}$ ) and  $\Omega$  type Es (foEs =  $4.0 \, \text{MHz}$ ) are affecting the upper layers respectively.

Interpretation: fbEs for c type is 3.4 MHz, while fbEs for L type Es which blankets the normal E layer is 3.1 MHz.

fbEs = 34 (for c type)

fbEs = 31 (for & type)

### @ Definition :

foFl is the ordinary wave critical frequency of the Fl layer. According to the magneto-ionic theory, the frequency separation

According to the magneto-ionic theory, the frequency separation between the ordinary and extraordinary mode traces is equal to about fB/2, where fB is the gyro-frequency (the frequency at which the electrons gyrate around the geomagnetic field). The value of fB varies depending on the location of the station and the ionospheric height concerned. In middle latitudes, it is about 1.2 MHz.

The Fl layer is formed during the daytime mainly in summer at heights above about 150 km. foFl varies from 4 to 6 MHz with the solar zenith angle in midlatitudes.

This layer sometimes appears in a complicated way under the influence of other stratifications (e.g. TID: Travelling Ionospheric Disturbance). In addition, it tends to be more stable in the diurnal variation, in contrast to the large depression of the F2 layer during the geomagnetic storm.

## @ Scaling accuracy:

foFl is scaled at the accuracy of 0.1 MHz (e.g. 4.5 MHz).

#### @ Indication of scaled value :

foFl is expressed by a numerical value with or without letters, or only a letter.

#### (Examples)


L --- The numerical value cannot be obtained due to the lack of clear cusp.

45S --- S is the descriptive letter (interference).

45UH --- U is the qualifying letter (doubtful), and H is the descriptive letter which indicates the influence of a different stratification. @ Notices for scaling:

- 1. The Fl layer is not observed throughout the year in the daytime. Therefore foFl is scaled only when the formation of Fl layer is recorded on the ionogram. When the Fl layer is not observed, the columns in the table should be left open for the parameters M(3000)Fl and h'F2 as well as for foFl.
- 2. In the case where such a transient stratification as the F0.5 layer is observed in the vicinity of h'F, the value of foFl is not necessarily scaled with the letter H (see R.H. p.20).
- 3. The short-lived traces like a transient layer or a oblique reflection should be neglected in scaling.
- 4. The value of foFl is closely linked with foE at midlatitude.

# foF1-1



(1)

Observation: This is a typical daytime ionogram in summer, although no Es trace is recorded. The E, Fl and F2 layers are fully stratified.

Interpretation: Since well-shaped cusps are seen at the critical frequencies of the Fl layer, foFl can be scaled with a sufficient accuracy required by the accuracy rules.

foFl = 46

Observation: The retardation at 6.5 MHz corresponds to foF2. No Fl trace is observed in this ionogram.

Interpretation: The Fl layer is observed only in the daytime except during 1-2 hours around sunrise or sunset. It cannot be observed in wintertime at higher mid-latitude stations.

Comment: The formation of the Fl layer is recognized by the change in curvature of the F region trace in the frequency range of about 3 - 6 MHz.

Observation: The change in curvature due to the Fl layer is observed near 5 MHz. The Es trace is of c type.

Interpretation: The Fl layer is not fully formed. Since no clear cusp is observed between the Fl and the F2 traces, foFl is expressed only by the descriptive letter.

foFl = L(48)

Comment: When only the letter L is applied, it is recommended to infer the approximate value of foF1 (4.8 MHz for this Case) from the monthly trend and to put it in the column of the scaling table. The letter L should be plotted at the place of the inferred frequency on the f-plot sheet.

Observation: foFl is scaled from the cusp at about 4.3 MHz, although
it is neither typical nor clear. The F2 layer trace has
horizontal parts which make easy in reducing h'F2.

Interpretation: The typical cusp as shown in dotted curve is expected from the well-developed Fl stratification. In cases where the degree of the cusp is equal to or less than this Case, the qualifying letter U is used with the descriptive letter L.

foFl = (foFl)UL = 43UL

Comment: When the shape of the ordinary and extraordinary wave traces is different from each other, the use of H instead of L is recommended as in the right: (foFl)UH


		**************************************		1				
(5)		······	y the Es				fmin	18
km   1 400	2 3	3Es	5 6	7 8 	9 10	llMHz	foE h'E foEs fxEs	315 110 74JA
300							h'Es Es type	80 115 e3
200		2Es—					fbEs foFl	74AA A
100		4					h'F h'F2	A A
	A fmin f	<b>A</b>		<u> </u>			foF2 fxI	A
		oE t of troo	es is mis	fxEs	4 - 41 -		<del>"</del>	<del></del>
(6)	absorptio	n Trace	es is mis	sing due	to the		fmin foE	50 B
400							h'E foEs fxEs	B 50EB
300 -				h'F2			h'Es Es type	В
200 -	an 	sorption		n'rz			fbEs foFl	50EB B
100 +					***************************************		h'F h'F2	В 250
				A			foF2 fxI	72R
( "	The Tri lea	fm		oF2	7 . 7 . 1 . 7			
(7) I	Ine ri ia. Es layer	yer is no	t observe	a being t	ranketed	by the	ſmin	18
400 -							foE h'E	A A
300				h'F2			foEs fxEs h'Es	72JA 78
200	2Es		Daniella a Sirian XIII				Es type fbEs	100 l2 45
		Es-l					foFl h'F	45UA A
100	A	Å	A	<b>a</b>			h'F2 foF2	300 63
	fmin	fbEs	foF2	fxEs			fxI	
<b>8</b> 1	he F regi	ion traces	s show the	e spreadi	ng		fmin	16
1.00			<b>滚</b> 旗				foE h'E	280 105
400 +				h'F2			foEs fxEs h'Es	56JA 62 120
300 —			h'F				n Es Es type fbEs	cl 28EG
200 —							foFl h'F	41F 220
100		Å					h'F2 foF2	315 60F
	fmin foE	foFl	fxEs	}			fxI	69
	тити гог	T OT T	TYPP					

(5)

Observation: Only the multiple reflections of the c type Es extending up to 8.0 MHz are recorded in the frequency range where the F layer echoes are expected.

Interpretation : It is interpreted that the F layer trace is totally blanketed by the c type Es. All the parameters for the F region are expressed by the letter A. foFl = A

Comment



This figure shows an example in which the blanketing takes place in the frequency range below 5 MHz. Only the parameters for the Fl layer are expressed by the letter A. foFl = A

**6** 

Observation: No trace is observed at all below 5.0 MHz. In addition the traces near the critical frequencies of the F2 layer are weaker than usual.

Interpretation: The cause of the disappearance of the trace below

5.0 MHz should be examined. When the cause is ascribed
to absorption, little interference is recorded. When
the cause arises from the interference, the influence
would be seen over the whole part of the height range.
This case is considered to be due to the absorption.

foFl = B

(7)

Observation: The £ type Es having up to the second order reflection is observed, fxEs = 7.8 MHz. Neither Fl nor E layer traces are recorded.

Interpretation : The traces below 4.5 MHz are blanketed by the 1 type
Es. Since the retardation at the low end of the F2
trace is clear, the value of foF1 can be deduced. The
numerical value is accompanied by the letter UA.

foF1 = (fbEs)UA = 45UA

(8)

Observation: The spreading of the Fl and F2 traces is observed. The c type Es is also seen.

Interpretation: The spreading of the Fl trace in the mid-latitudes is occasionally associated with ionospheric disturbances.

The descriptive letter F stands for the presence of spread echoes.

foFl = (foFl)F=4lF

For a doubtful value of foF1, foF1 = (foF1)UF.

Comment: For both the ordinary and extraordinary components, the width of the spreading along the frequency axis should be scaled and entered in the remarks column (e.g. 41 - 43 and 47 - 49 for this Case), for convenience of plotting in the f-plot sheet.

The cusps by another stratification than the regular one are seen in the Fl traces  1 2 3 4 5 6 7   8 9 10 11MHz	fmin foE	21 325
1 2 3 4 5 6 7 8 9 10 11MHz	h'E foEs	110 39
300 - h'F2	fxEs h'Es	140
200 h'F	Es type fbEs foFl	hl 33EG 47H
100	h'F h'F2	205 330
fmin foE foFl foF2	foF2 fxI	75
***************************************		
The shape of the ordinary component is not similar to that of the extraordinary one	fmin foE	21 335
branch trace	h'E foEs	110 58JA
300 h'F2	fxEs h'Es Es type	64 145 hl
200	fbEs foFl	34EG 44UH
100	h'F h'F2	235 350
<u> </u>	foF2 fxI	72 80X
fmin for forl fxes		
The trace is weak near the critical frequencies of the Fl and F2 layers	fmin	20
400	foE h'E	a a 38ja
300 h'F2	foEs fxEs h'Es	303А 44 100
200 h'F	Es type fbEs	33
100	foFl h'F	46R 200
4 4 4	h'F2 foF2	300 74R
fmin fbEs foFl foF2	fxI	
12 The Fl trace is missing (Lacuna Effect)	fmin	18
fminF	foE h'E	Y 110 G
	foEs fxEs h'Es	G G
300 h'F2	Es type fbEs	G
200	foFl h'F	46UY Y
100	h'F2 foF2	295 69
	fxI	-
fmin foE foF1 foF2		

#### foF1-3

9

Observation: There are two cusps at 4.3 MHz and 4.7 MHz (foFl)

in the ordinary wave trace (4.9 MHz and 5.3 MHz for the

extraordinary wave trace). Es is of the h type.

Interpretation: This kind of small cusp which seems to be caused by

the oblique reflection or the TID tends to appear in the vicinity of toF2 and move to the lower frequency range with the passage of time. The incidence of the cusp in upper frequency range of F1 trace is expressed by marking the numerical value with the letters UH, depending on the

accuracy. foFl = (foFl)UH = 47UH

Comment : When the cusp appears at the lower frequency range of the

Fl trace, there would be no direct influence on foFl, but on h'F.

Therefore, only h'F is indicated with the letter H.

(10)

Observation: The shapes of the ordinary and extraordinary components of the Fl trace are different from each other. In addition, the

F2 extraordinary wave trace shows a branch trace near the

critical frequency.

Interpretation: The slant reflection causes the discrepancy in the

shape of two component traces. Since it is interpreted that for is doubtful, for is expressed in a numerical value accompanied by the qualifying letter U and the

descriptive letter H.

foFl = (foFl)UH = 44UH

(11)

Observation: Upper parts (dotted\_curves) of the F1 and F2 layer traces disappear. The trace in the E region is only the £ type Es.

Interpretation: The missing part of the trace is considered to suffer

from the deviative absorption (letter R). Since the deviative absorption increases with the frequency, the trace may weaken with increasing frequency.

Depending on the frequency gap of the missing part, the scaling of foFl based on the accuracy rules is made.

foF1 = (foF1)R, (foF1)UR, (upper end of trace)DR,

or only the letter R.

In this case, foFl = 46R.

(12)

Observation : No trace is recorded in the frequency range from 3.2 MHz to 4.6 MHz. The lower part of the F2 trace suffers from the

retardation.

Y (Lacuna)

Interpretation: This is a typical example of the Fl Lacuna. Since the ionogram is obtained in the daytime, the trace in the E region is of the normal E layer and foE is inferred from the mean diurnal trend to a certain degree. foFl can be scaled from the retardation at the lower end of F2 trace with some ambiguity. Therefore it is expressed with the qualifying letter U (doubtful) and the descriptive letter

foFl = (fminF)UY = 46UY

Comment :

The Fl Lacuna, which extends from the normal E layer region up to the highest part of the Fl layer in this Case, is characterized by sudden disappearance of traces on the ionogram (As


for the details of Lacuna, see R.H. pp.53 ~ 57.)

### @ Definition :

The virtual height of the F layer, h'F, is defined as the lowest virtual height of the F layer ordinary wave trace.

In the daytime the F layer is offen doubly stratified into the Fl and F2 layers (Fig.a), while in the nighttime these two layers unite into one (Fig.b).

As h'F is always the lowest virtual height of any trace recorded in the F region, h'F = h'Fl in the daytime.



#### @ Scaling accuracy:

h'F is scaled with an accuracy of 5 km (e.g. 210 km or 255 km).

#### @ Indication of the scaled value :

h'F is expressed by the numerical value with or without letters, or only the letter.

(Examples)

A --- No F layer trace is seen being blanketed by the Es layer.

250EA --- E is a qualifying letter (less than), and A is a descriptive letter.

#### @ Notices for scaling :

- 1. h'F should be scaled even when the Fl layer is not observed in the daytime.
- 2. h'F is scaled from the horizontal part of the lowest major stratification in the F region. When the horizontal part is lost by Es blanketing or other reasons, h'F is expressed with a letter describing the reason.
- 3. The cross-reference to a sequence of ionograms obtained before and after the time in question usually helps to identify and scale some complicated trace including multiple Es reflections or slant echoes.

		***************************************						1			1		
	Tot	tal b	Lanke	ting	by t	he Es	laye	er				fmin	16
	1 2	2	3 4	۱ ،	5 (	5 7	7	8	9 10	1 17	MHz	foE	325
km		 			,	ĺ		l	, <u></u>	, <u>1</u>	11112	h'E	110
400 -				~~			***************************************					foEs	80JA
			***************************************	3Es			_					fxEs	86
300 -			l				· ·					h'Es Es type	110
				2Es								fbEs	c3 80AA
200 -	<del> </del>											foFl	A
												h'F	A.
100 -				-pro-								h'F2	A
	l k		<sub>   </sub>									foF2	A
	fmin	<u> </u>	<u> </u>				L	fxEs	<u> </u>	l		fxI	
<u> </u>			foE	` +h^	T to	000	vn +h						·
(2)	refl	ectic	n tra	ice fi	rom t	he Es	lay	e sec er	ond or	raer		fmin	16ES
					****		<del> </del>					foE	
	li	4Es										h'E	_
400 -	μ.						ļ					foEs	69JA
	tut.	3Es										fxEs	75
300 -	# T			9-74-21-23-10			1					h'Es	100 £4
	fer	2Es		Ì			And the second					Es type fbEs	14 51
200 -	18 🕇							ļ				foFl	ノユ
	ce											h'F	200A
100 -	-				Water to be a server							h'F2	
												foF2	74
<u> </u>	<u> </u>	<u> </u>	ll		<u> </u>		<b>A</b>					fxI	80X
<u></u>	fmin			fb			fxEs					······································	
(3)		er par .ayer	t or	the 1	r tra	ce 19	s bla	nkete	d by t	the	1		
		1	[	<u> </u>				<u> </u>	<u> </u>			fmin	LOEE
		ĺ										foE h'E	
400 -	<del> </del>											foEs	55JA
		3Es			//							fxEs	61
300 -	<u> </u>				Market Market							h'Es	110
		2Es		AND THE REAL PROPERTY.								Es type	f3
200 -	<u> </u>											fbEs	37
												foFl	00077
100 -	-					<b>_</b>						h'F	220EA
												h'F2 foF2	54
ļ	<u> </u>		<u> </u>			<u> </u>	<u> </u>	<u> </u>	<u> </u>			fxI	60x
fm	in		fbEs			Œs			2 3			· · ·	
4	Low Ee	er pa layer	rt of	the	r'l t	race	ıs bl	Lanke	ced by	r the		fmin	13
H	113	, <u></u>				<u></u>	T					foE	265
												h'E	110
400 -						<del> -</del>	1	<b> </b>				foEs	44JA
					•	1	1					fxFs	50
300 -	-		<u> </u>	//-		Second Second	<u> </u>					h'Es	120
		3		, "								Es type	c2
200 -	ļ	<u> </u>				<u> </u>						fbEs foFl	38 ha
		lb.				-						h'F	43 A
100	***************************************	-										h'F2	300
1.00												foF2	67
	A	A		A		<b>A</b>						fxI	0 1
	fmin	foE	f	oF1		foF	2						
<u> </u>								7					

(1)


Observation: The c type Es having multiple reflections extends up to 8.6 MHz. The F layer trace is not observed (Total blanketing).

Interpretation

: This kind of ionogram is frequently seen in the summertime (May - July) when Es activity is high. It is interpreted that the F layer trace is blanketed by the c type Es. All the parameters concerning the F layer are expressed by the letter A.

h F = A

Comment



In the case where only the Fl layer is blanketed as in the left figure, h'F2 and foF2 can be scaled, whereas h'F = A and foF1 = A.

(2)

Observation : The f type Es traces with multiple reflections are observed. foEs =  $6.9\ \text{MHz}$ . Lower end of the F trace merges into the Es trace.

Interpretation: The pattern like this case is frequently seen just before and after sunset. Careful examination of the width or slope of traces is helpful for discrimination between the F and Es traces. h'F is scaled with the letter A or letters UA, depending on the error involved in the scaled value.

h'F = 200A or h'F = 200UA

Comment : The interpretation described above is also valid for the scaling of h'F2.

(3)

Observation: The F trace below 3.7 MHz is blanketed by the f type Es.

The lower part of the F trace is not horizontal.


fbEs = 3.7 MHz.

nterpretation: Though this Case is similar to Case 2, it is very easy to discern the F trace from the second order reflection of the Es layer. h'F in this Case is expressed with the qualifying letter E (less than) and the descriptive letter A.

h'F = (h'F)EA = 220EA

If the slope of the lower end of the F trace is more steep, h'F = A is more appropriate.

Comment



In the left figure, it can be interpreted that h'F is affected by the Es even when there is a gap between fminF and foEs. h'F = A

4

Observation: The trace seen at the height of 120 km is of the c type Es. The Fl trace is not observed below 3.8 MHz.

Interpretation: If there were no influence of the Es layer, the Fl trace would be observed as the dotted curve. Since the slope of the Fl trace is steep, h'F is expressed only by the letter.

 $h^{\dagger}F = A$ 

If the slope of the trace is more moderate as seen from the dotted curve at around 3.6 MHz, h'F = 250EA.

(T) mh	ne trace	nartl	v di	sanne	ars c	าพากฮ	to t	he a	hsorn	t.i on		
(5) (D	Daytime)	par or	.y u		a. 5 (		60 0	nc a	naor b	01013	fmin	43
l .km	2	3 1	ļ :	5 6	<u> </u>	7 ,	8	9	10 1	lMHz	foE h'E	В
400						-		ļ			foEs	B 43EB
	***************************************					1/					fxEs	
300						h'	F2	<del> </del>			h'Es Es type	В
200	absor	ption				11 .					fbEs	43EB
200								-	<del>                                     </del>	<del></del>	foFl	L(48)
100 📙											h'F h'F2	220EB
											foF2	270 74
			<b>A</b> A			<b>A</b>					fxI	1 4
	ho P +			oFl		foF2						
(6) <sup>1</sup>	he F tra imit of	the i	onose	erved onde	irom	the	Towe	st I	reque	ncy	fmin	10EE
		11					<u> </u>				foE	
400											h'E foEs	10EE
											fxEs	エヘビル
300 📙											h'Es	E
	h'F										Es type	
200 +											fbEs foFl	10EE
											h'F	240EE
100 +								<u> </u>	<del>                                     </del>	<del> </del>	h'F2	
		A							-		foF2 fxI	33 39X
fmin		oF2	Thin .				·······	·				
(7)	The trac	e is	part:	ly lo	st o	<i>v</i> ing	to th	e ma	lfunc	tion		
	01 101103	. J.146			· · · · · · · · · · · · · · · · · · ·						fmin	19
						]					foE h'E	310C 110
400		1-5					/			+	foEs	39EC
200		faul									fxEs	C
300		[-t-]	77		7000 mm	h'	F2		-		h'Es Es type	С
200 —		<u>  `' </u>							***************************************		fbEs	39EC
								1	***************************************		foFl	45L
100 -		<u> </u>									h'F	C
			ا			ا ا					h'F2 foF2	275 78
	fmin		foF1			foF2	<u> </u>	L	1		fxI	10
© S	Small cus	ps ar		en in	the			t of	the	F1		
(8) t	race					- <del>-</del>	<u>,</u>	1		<del>-1</del>	fmin	14
											foE h'E	260
400					/			ļ		<del>                                     </del>	foEs	110 48
	1		NN		1						fxEs	54
300 🕂			/ }		-4	h'F2			-	1	h'Es	120
											Es type fbEs	cl 26EG
200										1	foFl	43
, , ,								Ì			h'F	205H
100										1	h'F2 foF2	295
	<u> </u>		A		Į.						fxI	70
fm	in foE	f	oF1		fo	F2						

5) Observation: Neither the trace nor the interference is observed in the frequency range below 4.3 MHz. fmin = 4.3 MHz

Interpretation: The cause of high fmin would be absorption. The slope of the Fl trace is so steep that h'F should be expressed only by the letter.

h'F = B (Absorption)

Comment: In the case where no trace is observed at all due to the strong absorption, the letter B is used for all parameters except Es type. Generally, it is important to identify the cause of no trace and then to select a suitable letter corresponding to the cause.

Observation: A typical nighttime ionogram. The F trace is observed from the lowest frequency limit (1.0 MHz) of the ionosonde.


Interpretation: Since the trace is not horizontal at the lowest limit of frequency, h'F is expressed by the numerical value with the qualifying letter E (less than) and the descriptive

h'F = (h'F)EE = 240EE

letter E (below the lowest frequency).

Comment :

(6)



When a gap is observed between the lowest limit of frequency and the lower end of the F trace as shown in left figure, it is usually caused by the absorption.

h'F = 220EB (or only the letter)

Observation: The trace is missing between 3.0 and 3.9 MHz. No Es

Interpretation: The trace within the frequency band is considered to be influenced by a defect in the ionosonde (C) or interference (S). The influence will usually extend over the full height range (0 - 500 km in this figure). Depending on the slope of the lowest part of the Fl layer ordinary wave trace, h'F is scaled as


h'F = C, h'F = (h'F)EC or h'F = (h'F)C.

Observation: Small cusps are seen in the lower part of the Fl layer traces (3.1 and 3.7 MHz). The Es layer is of the c type.

Interpretation: The appearance of an abnormal stratification usually influences the parameters of the normal layer. Therefore, since the numerical value is doubtful, it is expressed with the letters UH.

h'F = (h'F)UH = 205UH

Comment :



The trace separated from the Fl trace as shown in the left figure is not treated as the F layer trace, but a transient trace in the E region.

9 Oblique reflections are observed	fmin	15
1 2 3 4 5 6 7 8 9 10 11MHz	foE	A. )
km 400 2F	h'E foEs	60JA
F+Es ////	fxEs	66
300	h'Es	110
2Es	Es type fbEs	f2 27
200	foFl	
100	h'F h'F2	200
	foF2	52
fmin fbEs foF2 fxEs	fxI	58x
(10) Fl traces are very obscured (Fl Lacuna)	fmin	18
	foE h'E	Y 105
400	foEs	G
	fxEs	<i>a</i>
300 h'F2	h'Es Es type	G
200	fbEs	G
Lacuna	foFl h'F	46UY
	h'F2	Y 275
	foF2	70
fmin foF2'	fxI	
Es layer second order reflection is almost	· · · · · · · · · · · · · · · · · · ·	
conjunctive to the Fl trace	fmin	13
2F   2F	foE	290
400 3Es	h'E foEs	110
h F2	fxEs	39 45
300 + 2Es + / /	h 'Es	115
-h'F	Es type	c3 <i>l</i> 1
200 fbEs	fbEs foFl	39 49
100	h'F	230EA
	h'F2	350
	foF2 fxI	75
fmin foE foEs foFl foF2		
12 The echo spreading is seen in the F trace	fmin	16
	foE	
400	h'E foEs	16EB
	fxEs	1011
300	h'Es	В
h'F	Es type fbEs	16EB
200	foFl	
	h'F	2159
100	h'F2 foF2	65F
	fxI	71
fmin foF2		

9

Observation: A nighttime ionogram. The F traces other than the regular F traces with the second order reflection are observed at 210 km. Multiple reflections of the f type Es are also recorded.

Interpretation: The trace seen at 210 km is an oblique reflection which appears with the passage of a stant layer. When the vertical and oblique reflections are observed simultaneously at almost same height, it gives much confusion in the scaling. The cross-reference to the multiple reflection and the critical frequency as well as sequence of ionograms usually helps in scaling parameters.

h'F = 200

Comment : Attention should be paid to an oblique echo stronger than the normal one.

10

Observation: In the frequency range from 3.2 to 4.7 MHz, the normal E and Fl traces are very weak.

Interpretation: This is the typical FI Lacuna. The stronger the Lacuna effect, the more the FI trace becomes weak. h'F is expressed only by the descriptive letter Y.

 $h^*F = Y$ 

Comment : As for Lacuna, refer to Case 12 of foFl.

(11)

Observation: Two kinds of Es trace are observed. Multiple reflections of both c type Es and Fl layers are recorded.

foEs = 3.9 MHz (c type) foEs = 2.3 MHz (l type).

Interpretation: The Es second order reflection seems to be connected to the lower part of the Fl trace at 3.9 MHz (230 km in height). Careful examination of traces including multiple reflections is effective for avoiding misinterpretation.

In this Case the Fl trace starts from 3.9 MHz and h'F would be lower than 230 km.

h'F = (h'F)EA = 230EA

(12)

Observation: Both types of echo spreading are observed on this ionogram; one is the range type (the trace extends in the direction of the height) and the other is the frequency type (see Cases 17, 18 and 20 of foF2).

Interpretation: If the width of the trace near h'F exceeds 30 km it is regarded as the range type spreading and the descriptive letter Q is applied to the virtual height. Whether h'F = (h'F)Q or h'F = (h'F)UQ depends on the sharpness of the lower edge.


h'F = 215Q

Note

# h'F2

#### @Definition:

h'F2 is the minimum virtual height of the ordinary wave component of the highest stable stratification in the F region.



#### @Scaling accuracy :

 $h\,{}^{\prime}\,F2$  is scaled at the accuracy of 5 km (e.g. 300 km or 305 km). @Indication of scaled value :

h'F2 is expressed either by a numerical value with or without letters, or only by a letter.

#### (Examples)

- A --- expresses the presence of the blanketing effect of the Es layer.
- L --- as the descriptive letter, indicates that the foFl cusp is so smooth that the F2 layer height cannot be reduced accurately.
- 310EC --- The numerical value is affected by some instrumental reasons (C), and h'F2 should have a lower value (E) than 310 km.

#### @Notices for scaling :

- 1. When the stratification of the Fl layer is not observed, the column of h'F2 in the table is kept open.
- 2. h'F2 is scaled from the horizontal part of the F2 layer ordinary wave trace. When the horizontal part of the F2 trace is lost by some reason, a letter appropriate to express the reason is used according to the accuracy rules as written on pp.11 ∿ 12.
- 3. When the F2 trace extends down to the F1 trace without having the horizontal part at its lower end, the letter L is used. In this case, it is recommended to write an approximate range of height in the remarks column of the table.
- 4. Almost the same rules of scaling for h'F are applicable to h'F2.

# h'F2 - 1

Section   Sect			
1	(1) No Fl layer is observed (Daytime)	fmin	<u> 1</u> )4
h   1   1   1   1   1   1   1   1   1	3 2 2 h 5 6 7 8 0 30 33MTL-	foE	
100   100		h'E	
Section   Sect	400 +	foEs	23EG
200 100 100 100 100 100 100 100 100 100		fxEs	
Set type   fbEs   fbFs   fbF	300	h'Es	G
100		Es type	
100	200 h'F	fbEs	23EG
100			
## Comparison of the F1 layer is not enough   fmin   17			220
The formation of the F1 layer is not enough   fmin   17			
### Comparison of the F1 layer is not enough			68
2 The formation of the F1 layer is not enough    fmin		fxI	
Total   Control   Contro	imin 10E for 1 for 2	·	
foE 265 h F 110 foEs 27EK foEs fxEs h Es type fbEs 27EK foF1 L h F 205 h F 110 h F 205 h F 110 foF2 68 fxEs h Es type foF1 foF2  3 The cusp at foF1 is not fully developed  fmin 16 foE 2h5 h Es 110 foEs h Es type f foF1 foF2  400 h F 2 trace is observed (G condition)  fmin 21 foEs 330 h F 2 trace is observed (G condition)  fmin 21 foEs 330 h F 2 trace is observed (G condition)  fmin 21 foEs 330 h F 2 trace is observed (G condition)  fmin 21 foEs 330 h F 2 trace is observed (G condition)  fmin 21 foEs 330 h F 330 h F 330 h F 330 Es type c1 foEs 330 h F 330 Es type c1 foEs 330 h F 330 Es type c1 foEs 330 h F 330 FoEs 330 h F 330 Es type c1 foEs 330 h F 330 FoEs 330 h F 330 Es type c1 foEs 330 h F 330 FoEs 330 h F 330 Es type c1 foEs 330 h F 330 FoEs 33	(2) The formation of the Fl layer is not enough	fmin	ק ד. די ד
h   h   h   h   h   h   h   h   h   h			
100			
Thirp   Thir	1400		
100   1			27EG
Es type fbEs 27E foF1 L h'F 205 h'F2 L foF2 68 fxI  The cusp at foF1 is not fully developed  The cusp at foF2 lifes here foEs hore foF1 lifes as and here foF2 foF2 fxI  The cusp at foF1 is not fully developed  The cusp at foF1 is not fully developed  The cusp at foF1 is not fully developed  The cusp at foF2 lifes here foF2 foF2 fxI  The cusp at foF1 is not fully developed  The cusp at foF2 lifes here foF2 foF3 here foF4 here foF5			a
200	300		G
Top			OTTO
h'F   205   h'F2   L   foF2   68   foF1   foF2   68   foE   245   h'E   110   foEs   46   h'E   115   foF2   L   foF2   L   foF1   L   foF2   L   foF2   L   foEs   46   h'E   115   foEs   25   foF1   L   foF2   L   foF2   L   foF2   L   foF2   L   foF2   L   foF2   L   foEs   59   foEs   foEs   h2   foE	200		
100  A A A A A A A A A A A A A A A A A A			
The cusp at foF1   foF2   fxI   foF3   fxE5	100		
### A A A A A A A A A A A A A A A A A A			
### The cusp at foF1 foF2  The cusp at foF1 is not fully developed  ###################################			00
The cusp at foF1 is not fully developed	fmin foE foFl foF2		
fmin 16 foE 245 h'E 110 foEs 40 fxEs 46 h'Es 115 Es type c1 fbEs 25E foF1 L(44 h'F 210 h'F 210 h'F 259 fmin foE foEs foF2  4 No F2 trace is observed (G condition)  fmin 21 foE 330 h'E 110 foEs 42 fxEs 48 h'Es 130 foEs 330 h'E 110 foEs 42 fxEs 48 h'Es 25E		***************************************	
foE   245   h'E   110   foEs   40   fxEs   46   h'Es   115   fxEs   15   fxEs   25   fxE	(3) The cusp at fort is not fully developed	fmin	76
h'E   110   foEs   h0   fxEs   h6   h'Es   115   Es type   c1   foF1   L(hh   h'F   210   h'F2   L   foF2   59   fxI			
100			
100	1400		
h'Es   115   Es type   c1   fbEs   25E   foF1   L(44   h'F   210   h'F2   L   foF2   59   fxI	7,100		
200	300		
200			
foF1 L(44 h'F 210 h'F2 L foF2 59 fxI  Mo F2 trace is observed (G condition)  fmin 21 foE 330 h'E 110 foEs 42 fxEs 48 h'Es 130 Es type c1 fbEs 33E foF1 L(44 h'F 220	200 - h'F		25EG
100			L(44)
100 h'F2 L foF2 59 fxI  fmin foE foEs foF2  4 No F2 trace is observed (G condition)  fmin 21 foE 330 h'E 110 foEs 42 fxEs 48 h'Es 130 Es type c1 fbEs 33E foF1 44 h'F 225			
foF2 59 fxI  fmin foE foEs foF2  No F2 trace is observed (G condition)  fmin 21 foE 330 h'E 110 foEs 42 fxEs 48 h'Es 130 Es type c1 fbEs 33E foF1 44 h'F 225			
fmin foE foEs foF2  (4) No F2 trace is observed (G condition)  fmin 21  foE 330  h'E 110  foEs 42  fxEs 48  h'Es 130  Es type c1  fbEs 33E  foF1 44  h'F 225			
4 No F2 trace is observed (G condition)  fmin 21  foE 330  h'E 110  foEs 42  fxEs 48  h'Es 130  Es type c1  foF1 44  h'F 225	<u>}</u>		
1 min 21 foE 330 h'E 110 foEs 42 fxEs 48 h'Es 130 Es type cl fbEs 33E foF1 44 h'F 225			
foE 330 h'E 110 foEs 42 fxEs 48 h'Es 130 Es type cl fbEs 33E foFl 44 h'F 225	(4) No F2 trace is observed (G condition)	fmin	21
h'E 110 foEs 42 fxEs 48 h'Es 130 Es type c1 fbEs 33E foF1 44 h'F 225			
100 foEs 42 fxEs 48 h'Es 130 Es type cl fbEs 33E foFl 44 h'F 225			
fxEs 48 h'Es 130 Es type cl fbEs 33E foF1 44 h'F 225	400		
300 h'Es 130 Es type cl fbEs 33E foFl μμ h'F 225			
200 Es type cl fbEs 33E foFl 44 h'F 225	300		
200 fbEs 33E foFl 44 h'F 225			cl
foF1 44 h'F 225	h'F	fbEs	33EG
	[200		
1100 him			
	100	h'F2	G
			44EG
fxI	<u> </u>	fxI	
fmin foE foFl	fmin foE foFl		

Observation: A daytime ionogram. The normal E layer is seen while the Fl layer is not observed.

Interpretation: foFl cusp is usually expected near the frequency shown by the dotted line. But since no Fl layer is developed in this ionogram, columns for foFl and h'F2 in the table are kept open.

Comment: A transient layer which looks like the Fl trace sometimes appears at around sunrise or sunset. This kind of layer varies so fairly rapidly with time so that it is easily distinguished from the normal Fl layer. The occurrence of a transient layer is expressed by the descriptive letter H attached to h'F.

Observation: The F1 layer is not so fully developed as to be able to scale h'F2.

Interpretation: Although the F2 trace has no horizontal part, foFl may be inferred as 4.8 MHz with a considerable error from both the ionogram and the monthly mean value for the hour.

Since both h'F2 and foFl are doubtful, the letter L is to be used.

h'F2 = L and foF1 = L

Comment: When h'F2 is scaled as L, it is preferable to remark a probabbe range of height (from 270 to 315 km as shown by the mark † in the figure) in the table for convenience of the h'-plot.

Observation: The Fl layer is observed while the lower part of the F2 trace is not horizontal.

Interpretation: The scaling of h'F2 and foF1 is much easier than that in Case 2. foF1 would be in the vicinity of 4.4 MHz.

According to the accuracy rules, h'F2 is expressed either with the qualifying letter U (doubtful) and the descriptive letter L or with only the letter L for more developed F1 layer.

h'F2 = (h'F2)UL = 330UL or h'F2 = (h'F2)L = 330L

Observation: The F1 trace is clearly observed while the F2 trace is not recorded. foF1 = 4.4 MHz. The Es trace is of c type.

Interpretation: This kind of ionogram is often observed during the ionospheric disturbance associated with the geomagnetic storm, when foF2 decreases and h'F2 increases often in the morning as a typical case. Since this Case is interpreted that foF2 is equal to or smaller than foF1, the letter G is used (see Case 5 of foF2).

h'F2 = G

Comment :



This Case is a developed stage having a lower foF2 and higher h'F2 than in the left figure. In the interpretation of ionogram like this Case, there is also a case where the adoption of R may be more appropriate.

(5)	The Fl trace is blanketed and the lower part of the F2 trace is almost horizontal	fmin	17
	1 2 3 4 5 6 7 8 9 10 11MHz	foE	295
km 400 -		h'E foEs	110 71JA
	h'F2	fxEs	77
300 -		h'Es Es type	115
200 -	2Es	fbEs	c2 54
200		foFl h'F	A
100 -		h'F2	A 330
		foF2	69
	fmin foE fbEs foF2fxEs	fxI	
6	The lower F region is not observed owing to the	0 . 1	1.0
	absorption	fmin foE	48 В
1,00		h¹E	В
400 -		foEs fxEs	48EB
300 -	h'F2	h'Es	В
	absorption	Es type	48EB
200 -	absorption	fbEs foFl	40EВ
3.00		h¹F	В
100 -		h'F2 foF2	315EB 67
<b>,</b> .		fxI	ΟĮ
	fmin foF2		
7	F region traces in a frequency band are lost by the interference	2 .	0.7
		fmin foE	21 335
400 -		h'E	110
,00	nt int F2	foEs fxEs	42 46DS
300 -	<del>  </del>	h'Es	150
	rferenc	Es type	hl 34EG
200 -	The second secon	fbEs foFl	45
100 -		h†F	220
100		h'F2 foF2	340ES
	fmin foE foFs foF1 foF2	fxI	77
	fmin foE foEs foF1 foF2  The F2 trace seems to be present beyond the upper limit of the height range		
(8)	limit of the height range	fmin	19
		foE h'E	325 110
400 -		foEs	33EG
200	/ //	fxEs h'Es	G
300 -		Es type	J
200 -	h'F	fbEs	33EG
		foFl h'F	<b>51UW</b> 225
100 -		h'F2	227 W
		foF2 fxI	W
A	fmin foE foFl	TYŢ	
			<del></del>

5


Observation: The c type Es extends up to 7.7 MHz. The F trace below 5.4 MHz is not seen at all.

Interpretation: The F trace below 5.4 MHz is blanketed by the Es layer.

Since the lower part of the F2 trace is horizontal, there
is no difficulty in scaling h'F2.

$$h'F2 = 330$$

Comment



h'F2 depends on the slope of the F2 trace at its lower end.

h'F2 = (h'F2)EA = 330EA

If either the slope is larger than that of the trace in the left figure or the F2 trace is totally blanketed, the letter A is used.

h'F2 = A

6

Observation: Only the F2 trace is observed. There is no trace below  $4.8~\mathrm{MHz}$ .

Interpretation: The recorded trace is the F2 one, being judged from the height and critical frequency. It is considered in this Case that the lack of lower traces is caused by the absorption (B) rather than by the defect of the ionosonde (C) or the interference (S). Since the lower part of the F2 trace is not horizontal and there exists rather high absorption, the qualifying letter E (smaller) and the descriptive letter B should be attached to a numerical value.

$$h'F2 = (h'F2)EB = 315EB$$

Comment: When no traces are recorded on the ionogram, the cause of the lack of traces should be examined. A letter suitable for the cause is to be used.

7

Observation: No traces are seen between 4.6 and 6.5 MHz. The Estrace is of h type foEs = 4.2 MHz.

Interpretation: The traces in the central part of the record are lost owing to the interference. The value of h'F2 is scaled according to the slope of the F2 trace at its lower end, being based on the scaling rules as follows:

h'F2 = (h'F2)ES = 340ES

h'F2 = (h'F2)US = 340US

h'F2 = 340 (The trace is horizontal)

h'F2 = S (The slope of the trace is steep)

8

Observation: The F2 trace can not be identified within the maximum height limit of record. foFl = 5.1 MHz.

Interpretation: When the existence of the F2 trace in a height above the maximum height is inferred from the reference to the sequence of records, the descriptive letter W is used.

$$h'F2 = W$$

The maximum height of the ordinary ionogram is about  $800\, \, \sim \, 1000 \, \, \text{km}.$ 

Comment: Attention should be paid to the difference between the G condition as illustrated in Case 4 and the W condition in this Case.

#### @ Definition :

foF2 is the ordinary wave critical frequency of the highest stratification in the F region. This definition, however, is not valid for the case where foF2 decreased down to a value less than foF1, known as the G condition which sometimes occurs during the geomagnetic storm.

foF2 is the most important parameters for telecommunication applications.

According to the magneto-ionic theory, the frequency separation between the ordinary and extraordinary mode traces is equal to about fB/2, where fB is the gyro-frequency (the frequency at which the electrons gyrate around the geomagnetic field). The value of fB varies depending on the location of the station and the ionospheric height concerned. In middle latitudes, it is about 1.2 MHz.

### @ Scaling accuracy :

foF2 is scaled at the accuracy of 0.1 MHz (e.g. 8.2 MHz).

#### @ Indication of scaled value :

foF2 is expressed either by the numerical value and/or the letters. (examples)

- S --- The numerical value cannot be obtained owing to the interference.
- 62S --- There exists the interference not affecting the accuracy of the numerical value.
- 62US --- The numerical value is affected by the interference.

  U is the qualifying letter (doubtful).

#### @ Notices for scaling :

- 1. A transient layer which sometimes appears near foF2 is usually associated with the travelling ionospheric disturbances. In scaling such a layer, the cross-reference to a sequence of ionograms obtained before and after the time concerned is usually very helpful.
- foF2 must not be scaled from the oblique reflection trace.
- 3. The reference to the accuracy rules (pp. 3 4) is particularly desirable in scaling foF2.
- 4. The rules to be applied when foF2 is scaled by extrapolation are summarized on the following pages. See R.H. PP. 35 39 for more details as well.
- 5. The scaling rules of the spread echoes are given in detail on pp. 58 63 (Definition of spread F types) and pp. 75 78 (letter F) of R.H.

# Extrapolation

In the case where the trace near the critical frequency is not clearly recorded owing to the interference, defect of the ionosonde or some ionospheric reasons (e.g. absorption or scattering), it is recommended to obtain the most reliable value of foF2 by extrapolation. Extrapolation can be made by extending hypothetically the traces up to the most probable value of the critical frequency. Since the accuracy of extrapolated value depends necessarily on the amount of extrapolation, the accuracy rules (see pp. 3 - 4) should be applied to in scaling as described in the following examples.


In order to obtain the most probable value by extrapolation, it is important to imagine the most typical shape of retardation near the critical frequency. In doing this, cross-reference to the ionograms obtained in similar conditions is useful, although the shape of the trace is not always the same.

#### @ Examples:

Four cases are illustrated to obtain  $8.0~\mathrm{MHz}$  of foF2 by extrapolation. Upper parts of the F trace are assumed to be lost by interference (S) in these examples, although there are actual cases where R (attennation) may be appropriate. An " a" in the explanation of figures denotes the percentage of extrapolated part relative to  $8.0~\mathrm{MHz}$ . The use of the qualifying letter is defined in the accuracy rules.


(R)

### Extrapolation




@ The highest frequency of the trace recorded is 7.9 MHz. The extrapolated frequency range (0.1 MHz) is less than 2% of 8.0 MHz. The descriptive letter S is attached to the numerical value.

$$foF2 = 80S$$




@ The highest frequency of the trace recorded is 7.7 MHz. The extrapolated frequency range (0.3 MHz) is about 4% of 8.0 MHz. Since 2% < a < 5%, the numerical value is followed by the qualifying letter U (doubtful) and the descriptive letter S.

$$foF2 = 80US$$



@ The highest frequency of the trace recorded is 7.0 MHz. The extrapolated frequency range (1.0 MHz) is about 13% of 8.0 MHz. Since 10% < a < 20%, the numerical value is followed by the qualifying letter D (greater than) and the descriptive letter S.

$$foF2 = 70DS$$



@ The highest frequency of the trace recorded is 6.0 MHz. The extrapolated frequency range (2 MHz) is 25% of 8.0 MHz. Since a exceeds 20%, only the descriptive letter is used.

$$foF2 = S$$

# foF2 -1

(1)	No F2	trace is layer	obse	rved	owin	g to	the bla	nketi	ing by	finin	16
	1 2		4	5 (	5 , 7	7 {	3 9	10	11MHz	fmin foE	325
km 400 -			<u> </u>			ļ			1111112	h'E foEs	110
700		***************************************			/				Printed to A Avenue of the Control o	fxEs	79JA 85
300 -										h'Es	115
			•			2E	3			Es type fbEs	c2 79AA
200 -					***************************************					foFl	A A
100 -			at a management of the same	P-W-72-CC-04-FB-W-W-B-S	**************************************		> <del></del>			h'F h'F2	А
100										foF2	A A
	fmin	foE	<u> </u>		<b>A</b>					fxI	n
		the extra	aordin	narv	foF2	nent	fxEs	erved	in the	9	
(2)	F reg	ion owing	g to	the b	lanke	ting	by the	Es l	ayer	fmin	10EE
			İ	{ !	1				The contract of the contract o	foE h'E	
400 -				·;	<del>/</del> _					foEs	60
	3Es -	wkwidowedCOOddeCoOoceCOCcompanies.co		_ 2						fxEs	66
300 -										h'Es Es type	115 <b>f</b> 3
200 -	2Es			*********						fbEs	60AA
200 .										foFl	,
100	A TRANSPORT OF THE PROPERTY OF	MCMACOCCIOCO	AUTHOLISMIN STREET	Michellan and Company						h'F h'F2	A
					ı					foF2	59JA
fm	in			fol	ds fx	Fe				fxI	65X
	Lowe	part of	trac				owing	to th	e		
3	absoi	rption								fmin	53
						;				foE	В
400	-					<u> </u>	,			h'E foEs	В <b>7</b> 3
						/				fxEs	79
300										h'Es	115
200		bsorptic	n							Es type _ fbEs	cl 73
200										foFl	В
100	<u> </u>									h'F	B A
				٨						h'F2 foF2	а 79R
			<u> </u>	min	fo	Es f	oF2			fxI	, ,
	The ur	per part defect						uptly	owing		
(4)	to the	defect	of th	e ion	roson	de"			I	fmin	20
				İ						foE h'E	315 110
400										foEs	32EG
			IN					And the second s		fxEs	G
300			ノブ	140	ult					h'Es Es type	G
200				ı lı a	ulb					fbEs	32EG
200		<u> </u>								foFl h'F	43 230
100	490	_//								h'F2	230 2950
									e de la constante de la consta	foF2	Ć
<u> </u>	fmir	<u> </u> ≱ 1 foE	♠ foFl		<u> </u>	<u> </u>	<u> </u>	1		fxI	
L	J. HLL.I	T TOE	1 OT, T								

# foF2-1

Observation: The c type Es having the second order reflection extends up to 8.5 MHz. The F layer is entirely blanketed by this Es layer.

Interpretation: A value of foF2 predicted from the sequence of ionograms should be compared with foEs. Since the foF2 is smaller than foEs in this Case, it is considered that the F2 layer is blanketed by the Es layer. Therefore, the letter A is used.

foF2 = A

Comment: As for the derivation of foEs from ftEs recorded, see Cases 7 to 16 of foEs.

Observation: The f type Es is so intense that it entirely blankets the ordinary component of the F trace. foEs = 6.0 MHz

Interpretation: The F trace above 6.0 MHz is supposed to be the extraordinary component, judging from a sequence of ionograms. The value of foF2 which can be derived from fxF2 is expressed with the qualifying letter J and the descriptive letter A.

foF2 = (fxF2 - fB/2)JA = 59JA

Comment: When foF2 derived from fxF2 is greater than foEs, the descriptive letter A is not appropriate. In such a case, the use of the letter S or R should be taken into account depending on the presence of the interference.

Observation: No trace is recorded below 5.3 MHz. fmin = 5.3 MHz.

Interpretation: There is so intense absorption that fmin is high and the F2 trace is also weak.

foF2 = (foF2)R = 79R

Comment: When only one component of the F2 trace is recorded, the decision whether it is the ordinary component or not is to be made by utilizing a sequence of ionograms.

The extraordinary component usually suffers from much more absorption than the ordinary. When no trace is recorded at all,

all parameters are expressed by the letter B.

Observation: The Fl trace is clearly recorded but the traces above 5.5 MHz are lost abruptly.

Interpretation: The disappearance of traces would be caused by the defect of ionosonde. Therefore, the letter C is appropriate.

foF2 = C

Attention should be paid to the difference between S (interference) and C conditions.

Comment: The ionogram produced by a malfunctioning ionosonde is not so simple. For example, the following cases are expected to occur: The trace disappears entirely or sometimes partly. The background noise disappears completely. The traces appear intermittently. The height of traces change irregularly. The frequency or height markers are not normal.

3

# foF2 - 2

(5) No F2 trace is recorded (G condition)	fmin	20
1 2 3 4 5 6 7 8 9 10 11MHz	foE	320
km	h'E	110
400	foEs	37
300	fxEs	43
300	h'Es Es type	125
200	fbEs	cl 32EG
	foF1	42
100	h'F	210
	h'F2	G
	foF2 fxI	42EG
fmin foE foFl	IVI	
(6) foF2 is very close to foF1		
0 1011 15 Very Crose to 1011	fmin	18
	foE	370
500	h'E foEs	110
	roes fxEs	51 57
height range: 100-600 km	h'Es	57 115
	Es type	cl
300	fbEs	43
	foFl	46
200	h'F h'F2	230EA
	foF2	560 47
100	fxI	41
fmin foE foF2 foEs		
Unusual cusp by a stratification other than the F2		
U layer is seen in the F trace (Nighttime)	fmin	10EE
	foE	
400	h¹E	
	foEs	10EE
300	fxEs	
	h'Es Es type	E
200	fbEs	10EE
	foFl	ئىدىنىد ب سى
100	h'F	220
	h'F2	
<u> </u>	foF2	57H
fmin foF2	fxI	63X
The cusp by a transient stratification is seen near the F2 layer critical frequency		_
Come is rayer critical rieddench	fmin	16
cusp /	foE h'E	300 110
400	n E foEs	40JA
	fxEs	465 M
300	h'Es	115
	Es type	cl
200	fbEs	31
	foFl h'F	43 220
100	h'F2	315
	foF2	79H
	fxI	12-
fmin foE fxEs foF2		

(5)

Observation: The trace in the F region on this ionogram is not that of the F2 layer but of the F1 layer. foF1 = 4.2 MHz. The Es trace is of c type.

Interpretation: The F2 layer is in the so-called G condition which usually occurs during ionospheric disturbances associated with the geomagnetic storm. It corresponds to the condition that the electron density in the F2 layer becomes equal to or lower than that in the F1 layer. foF2 is expressed by the numerical value of foF1 with the qualifying letter E (smaller) and the descriptive letter G.

foF2 = (foF1)EG = 42EG

Comment:

Attention should be paid to the following two confusing cases: One is the case where the F2 trace disappears owing to either the interference or the attenuation. The other is the case where the trace cannot be recorded because of its extremely high virtual height exceeding the limit of height range (see Case 15). The letter S or R is suitable for the former while the letter W is suitable for the latter.

**(6)** 

Observation : The F2 trace has a height of 560 km and the F1 trace is partly absorbed. foF1 = 4.6 MHz.

Interpretation: The ionogram like this case is often seen just before or after the time when the ionogram like Case 5 is observed.

Attention should be paid to the trend of the virtual height change which is apt to be overlooked.

foF2 = 47

Comment :

When foF2 approaches closer to foF1 with time, use of the letter G is usually appropriate. On the other hand, when the virtual height of the F2 trace increases with time keeping some separation of frequency, the letter W is to be applied.

(7)

Observation: Nighttime ionogram having an unusual cusp near 4.4 MHz.

Interpretation: Almost all such cusps appear suddenly and vary quickly.

The appearance of this kind of stratification usually affects the critical frequency and even the virtual height.

Therefore, even when no effect is expected on the accuracy of scaled value, the letter H should be attached to the numerical value.

foF2 = (foF2)H = 57H

Comment:

In this ionogram, h'F which is not influenced by the stratification should not be accompanied by the letter  ${\tt H.}$  In the daytime, attention should be paid not to confuse such a cusp with foFl.

(8)

Observation: Daytime ionogram. An abnormal cusp (appearance of a stratification) is observed at 7.4 MHz of the F2 layer ordinary component.

Interpretation: The cusp which appears near foF2 tends to move towards lower frequencies with time. When the transient stratification influences foF2, the letter H is attached.

foF2 = (foF2)H = 79H

Comment :



In the left figure, foF2 should be scaled from the solid trace in lower frequencies rather than from the higher thin trace which might be a transient reflection.

The trace near the F2 layer critical frequency is		
9 The trace near the F2 layer critical frequency is absorbed	fmin	21
1 2 3 4 5 6 7 <u>1</u> 8 9 10 11MHz	foE	310
km 400	h'E	110
1400 d d	foEs fxEs	31EG
300 tennua t	h'Es	G
300	Es type	G
200	fbEs	31EG
	foFl	L(52)
	h'F	215
100	h'F2	270
	foF2	78UR
fmin foE foF1 foF2	fxI	
masked by the interference	fmin	loee
	foE	
400	h'E	
	foEs	loee
300 nt territ	fxEs h'Es	E
300	Es type	10
	fbEs	10EE
200	foFl	
	h'F	210
	h'F2	
	foF2	33DS
fmin foF2	fxI	S
C Umara mark of the EO trans is such at the	· · · · · · · · · · · · · · · · · · ·	
Upper part of the F2 trace is masked by severe interference		
	fmin	20
	foE h'E	315 110
400	foEs	40
	fxEs	. •
300	h'Es	125
	Es type	cl
200 nteri	fbEs	32EG
	foFl	45UL
	h'F	250 300
	h'F2 foF2	300 77JS
	fxI	1100
fmin foE foF1 foF2 fxF2		······································
12 A fork-shaped trace is observed	fmin	16ES
	foE	TOHO
	h'E	
400	foEs	16ES
	fxEs	
300 - 9	h¹Es	S
	Es type	3 / m~
200 - rencci - land	fbEs	16ES
	foFl h'F	250
100	h'F2	<i>L</i> ) U
	foF2	44V
	fxI	51X
fmin foF2 fxF2		-

9

Observation: Uppermost parts of the F2 trace are not recorded.

The cusp of foFl is not clear, while the normal E layer is

Interpretation: It is interpreted that both components of the F2 trace are weakened by the attenuation (R) near 7.4 and 7.7 MHz respectively. Since foF2 extrapolated by extending the trace as dotted curve differs roughly 5% from the top frequency recorded (7.4 MHz), the qualifying letter U is

foF2 = (foF2)UR = 78UR

Comment: The attenuation (correctly, the deviative absorption) in the F region increases as the retardation does. This is also true for the Fl and E traces.

(10)

Observation: Nighttime ionogram in which the F trace is observed from 1.0 MHz. No trace, however, is recorded in the frequency range above 3.3 MHz owing to the interference.

Interpretation: The value of foF2 is obtained by assuming the shape of trace as the dotted curve (extrapolation). Then an appropriate qualifying letter is looked for depending on the quantity extrapolated. Since the quantity  $(4.1-3.3=0.8\ \text{MHz})$  does not exceed 20% of foF2 (4.1 MHz) in this case, the letter D is appropriate according to the accuracy rules of extrapolation.

foF2 = (Upper limit of observation) DS = 33DS If the quantity exceeds 20%, only the descriptive letter is used.

foF2 = S

Comment : As for the accuracy rules of extrapolation, see pp. 90-91 of this Manual.

(11)

Observation: The traces in the frequency range from 6.5 to 7.7 MHz are not clear, while the traces of the normal E and the Fl layers are clearly observed.

Interpretation: The traces are obscured by the interference (S).

Since the extraordinary component of the F2 trace is seen,
foF2 is deduced from it. Therefore, the letters J and S
should be used.

foF2 = (fxF2 - fB/2)JS = 77JS

(12)

Observation: A fork-shaped F2 trace is observed.

Interpretation: It is easily understood that the F trace consists of two pairs of the ordinary and extraordinary components (one pair is 4.4 and 5.1 MHz, and the other is 4.2 and 4.8 MHz). The pair at higher frequencies should be scaled with the descriptive letter V, as representing the critical

frequency. Therefore,

foF2 = (foF2)V = 44V

Comment :

This type of trace is rarely observed in the sense that some of the four prongs are usually missing. When the ordinary component is missing, foF2 can be deduced from the extraordinary trace. It should not be confused with the oblique reflection, the spread echo or the different stratification. It is recommended to scale and write in the Remarks column of the scaling sheet the critical frequencies of four prongs, because they are needed in the plotting.

# foF2-4

		·····	
13	The trace disappears suddenly near the F2 layer critical frequency	fmin	16
	1 2 3 4 5 6 7 8 9 10 11MHz	foE	275
km 400 -		h'E foEs	110 42JA
700		fxEs	42JA 48
300 -		h'Es	120
		Es type	cl .
200 -		fbEs foFl	28EG L(49)
		h'F	230
100 -		h'F2	315
		foF2	90EY
	fmin foE foEs foFl	fxI	
60	The Fl and F2 traces are computat deformed from		
(14)	a typical shape	fmin	18
		foE h'E	340 110
400 -		foEs	34EG
		fxEs	
300 -		h'Es	G
		Es type fbEs	34EG
200 -		foFl	53UH
7.00		h'F	220
100 -		h'F2 foF2	305
		fxI	91JH
	fmin foE foFl foF2 fxF2		İ
(15)	The upper part of the . F2 trace exceeds the height		
	limit of the ionogram / /	fmin	16
		foE h'E	295
500 -		foEs	110 30EG
	height range: 100-600 km	fxEs	
400 -		h'Es	G
200		Es type fbEs	30EG
300 -		foFl	44
200 -		h'F	215
		h'F2	540
100-	A A SOUTH FORTH	foF2 fxI	56UW
	fmin 10F1 10F2		
16	The z component is observed in the F trace	fmin	16ES
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	foE	<del>_</del>
400 -		h'E	3 6EG
-700		foEs fxEs	16ES
300 -	interference	h'Es	s
		Es type	, /
200 ·		fbEs foFl	16ES
	10ce	h'F	230
100 -		h'F2	
		foF2	44Z
	fmin fzF2 foF2 fxF2	fxI	53
	THILL TOOL TOLK TWIL		

#### foF2-4

(13)

The trace near the F2 layer critical frequency (above 8 Observation : MHz) is abnormal in shape and both components suddenly disappear in the vicinity of 9 MHz. The F1 trace is also not

Interpretation: When the layer tilt is large, the trace approaching up to foF2 sometimes disappears suddenly. Since such trace is the reflection from an oblique direction, foF2 should not be derived from it. foF2 is to be represented by the limiting value accompanied by the qualifying letter E (smaller) and the descriptive letter Y.

foF2 = (limiting value) EY = 90EY

The letter H is generally used to indicate the presence of a stratification or a tilted layer, whereas the letter Y expresses the presence of severe tilt in the F region. Note t the meaning of Y is different from that for Lacuna (see Case 12

(14)

Observation: The ordinary components of F1 and F2 layers show some deformation, resulting in an unusual cusp at foFl and insufficient separation (0.3 MHz) of o and x components near foF2,

Interpretation: When there is an ionospheric tilt in N-S direction. the recorded frequency separation between the o and x components may differ usually from fB/2, and sometimes one component is modified in shape. In this case, since the extraordinary component is normal, foF2 can be deduced from fxF2 as dotted curve.

foF2 = (fxF2 - fB/2)JH = 91JH

For the layer tilting in E-W direction, no significant Comment : difference is expected between shapes of both components.

(15)

The virtual height of the F2 trace is so high (540 km) Observation: that the traces near the F2 critical frequencies are beyond the maximum height range (600 km in this Case).

foF2 = (foF2)UW = 56UW

Interpretation: Since the height limit of ionosonde is about  $800\, \sim\, 1000$ km, the ionogram like this Case is not likely to be seen Only in the case where traces seem to still actually. exist at a height exceeding the height limit, the letter W can be applied (refer to Cases 5 and 6).

> The portion of trace outside the height limit should be extrapolated being based on the accuracy rules. When the letter W is applied, the numerical value is to be followed by the letters D or U.

Observation: The F traces are split into three branches (z, o and

(16)

x components). Interpretation : The critical frequency seen at 3.8 MHz is of the z

mode which is the third magneto-electronic component propagating along the geomagnetic field line. of ionogram is not so common, since the field line runs far from the vertical in mid-latitudes. Slight spreading is seen on both ordinary and extraordinary components. difference between fxF2 and fzF2 is equal to fB (the gyrofrequency), with foF2 occurring about the middle of both components. The appearance of the z component is expressed by the letter Z.

foF2 = (foF2)Z = 44Z

Comment :

Both of the descriptive letters Z and F are applicable to this case. Concerning the selection of letter, follow the selection rules described in 3.2 on page 67 of R.H.

	Both	ordi	narv	and e	extra	ordir.	arv (	. Ompo	nent	ടറ്	the	<u> </u>	
(17)	Ftr	ace a	re in	spre	ead c	ondit	ion		TICITO	s of	OTIC	fmin	15
lzm	1 2	2	3 !	ļ	5	6 '	7	8	9	10 1	lMHz	foE h'E	
km 400		ļ	ļ	层层	ļ	ļ. <del></del>		-		_		foEs	15EB
			,	<i>\ \</i>	1							fxEs	
300				<i></i>	<del></del>	<del>                                     </del>						h'Es Es type	В
200												fbEs	15EB
200											1	foFl	-
100						ļ						h'F h'F2	550
	1									i		foF2	LIUF
	fmin	İ	£	<b>l⁴</b> oF2	f <sub>xI</sub>	<u></u>		<u> </u>		<u>.</u>		fxI	51
60		7 tra					the f	redu	encv	axıs			
(18)	(Free	uenc	y-typ	e)	7			, I Cqu				fmin	12
												foE h'E	
400 -				ļ	ļ <u>ķ</u> : ;					_		foEs	12EB
1					<i> </i> :::::							fxEs	
300 -				<i></i>	(				-		<del> </del>	h'Es	В
000		_							-			Es type fbEs	12EB
200					<b>⊸</b> h'	F		<u> </u>		_	1	foFl	
100 -			W								İ	h¹F	200
100												h'F2 foF2	52F
	A				<u> </u>	<u> </u>	<u> </u>					fxI	67
	min		4		oF2	fxI							
(19)	The F (Range	trac e-typ	e is e)	spre	ad al	ong t	ne ne	eignt	axı	S			14
									T			fmin foE	14
400 -						L.,						h'E	
400							***					foEs	13EB
300 -									ļ			fxEs h'Es	В
				<u> </u>	نبعنيذ	بسنة بسنا						Es type	ı,
200 -					<u> </u>	' F'						fbEs	13EB
												foFl h'F	220Q
100 -									<u> </u>	-	-	h'F2	220 W
	Δ		***************************************					A				foF2	୍ଦ
	fmin		1	!	<u> </u>		<u></u>	fxI		!		fxI	84
20	The f inter	reque ferer	ency- nce	type	sprea	ading	infl	uence	ed by	the		fmin	16ES
			***************************************		ļ		1	<u> </u>	T		<u> </u>	foE	
400 -			<u>;</u> j. j.									h'E	· /
, ,,,,	77		1//	iii i	ìnt							foEs fxEs	16ES
300 -	interference		2 minutes and the second		L:0				ļ		ļ	h'Es	s
-	rfe				rfe				:			Es type	n (
200 -	Trei H			<u>                                     </u>	rferenc						-	fbEs foFl	16ES
	nce				nce							h'F	270ES
100 -				1				<b> </b>				h'F2	-
	<sub>&amp;</sub>				la							foF2	F
ļ	fmin		L	f:	κI	I	L				<u></u>	fxI	51
L													

17

Observation : Interpretation :

Echo spreading is seen for both components of the F trace. In this Case, the inner edge (lower side of frequency) of each component is clear and the traces spread towards higher frequencies. The main trace is in the clear-cut Therefore, foF2 = 4.1 and fxF2 = 4.7. Since the width of the echo spreading exceeds 0.3 MHz which is the threshold value for indicating the presence of echo spreading, the numerical value is followed by the letter F. The echo spreading brings basically error in scaling to some extent. Therefore, the letter U is usually applied together with the letter F. foF2 = (foF2)UF = 41UF.

Comment



As shown in the left figure, if the outer edge (higher side of frequency) of each component is observed clearly, this should be regarded as the main trace from which foF2 can be scaled. The case of clear inner edge is more common than that of clear outer edge. The width of the spreading is to be noted for both components in the Remarks column of the scaling sheet.

(18)

The maximum width of the echo spreading along the frequency Observation: axis is about 1.5 MHz (5.2  $\sim$  6.7 MHz).

This kind of spread pattern is called the frequency-Interpretation: type spreading. The clear inner edge would be the main trace from which foF2 is scaled, provided that the F layer is horizontally stratified.

foF2 = (foF2)UF = 52UF

If there is a clear trace from which fxF2 is scaled, foF2 may be deduced from it.

foF2 = (fxF2 - fB/2)JF

The width of the echo spreading (5.2  $^{\circ}$  6.7 MHz) is noted in

the Remarks column.

The second order reflection is conveniently used in identi-Comment fying foF2, since it is likely to be observed more clearly (without the spreading) than the first.

(19)

Observation: The echo spreading occurs mainly along the height axis.

> The virtual height of the trace increases very slowly with frequency.

Interpretation: This kind of spread pattern is called the range-type It is difficult to scale foF2 from this type of ionogram which does not show the presence of clear main trace. Thus, for this Case, foF2 is expressed only by the letter Q.

foF2 = Q

The width of the spreading (1.4  $\sim$  8.4 MHz) is noted in the Remarks column of the scaling sheet. For expressing the presence of the range-type spreading, h'F is followed by the letter Q.

(20)

A nighttime ionogram. Observation: The echo spreading is seen above The interference effects on the observation in both 2.6 MHz. frequency ranges below 1.7 and above 4.3 MHz.

This is an example of frequency-type spreading. Interpretation: frequency range with the spreading is so wide that only the letter F is eligible.

foF2 = F

Comment


Attention should be paid, when severe interference covers the whole frequency range. Generally speaking, if two causes affect on the scaling, the priority is to be given to the bigger Therefore, the following two scalings are correct depending on the situation concerned.

foF2 = FS or foF2 = SF

#### @ Definition :

The parameter fxI is defined as the highest frequency at which the reflection from the F region (Fl or F2 layer) is recorded, independent of whether it is reflected from vertical or oblique directions (note that parameters other than fxI should not be scaled from oblique reflections).

'fxI is a parameter indicating the presence of the F layer scattering which contributes to an actual propagation at oblique incidence. fxI is also applied to the polar or equatorial spurs, but not applied to traces of ground backscatter.



- G: Ground backscatter tangential to the second order F reflection.
- M: Es backscatter tangential to the M(2F-Es) trace which is described in detail in Appendix 1 (p.118 of this manual).

### @ Scaling accuracy :

fxI is scaled at the accuracy of 0.1 MHz (e.g. 4.3 MHz).

#### @ Indication of scaled value :

fxI is expressed either by the numerical value with or without the letter, or the letter only.

#### (Examples)

- A --- The descriptive letter expressing that the F trace is blanketed by the Es layer.
- 93 --- The highest frequency of the spread F trace.
- 45X --- X is the descriptive letter expressing the fxI is equivalent to fxF2 in the absence of the echo spreading.

#### @ Notices for scaling :

- 1. fxI should be scaled from the ionogram observed with the normal gain of the ionosonde receiver.
- 2. Concerning the frequency separation between the ordinary and extraordinary components as necessary for deciding fxI, see Definition of foFl on p. 67.
- In the scaling of fxI, the descriptive letters A, B, C, D, E, G, S and Y can be applied (for details, see pp. 102-103 of R.H.). The scaling of fxI is classified into the following two cases:
  - a. In the presence of the echo spreading and/or the oblique reflection in the F region, the highest frequency is scaled as fxI including the letters attached.

#### (Examples)

fxI = 55

fxI = 50X, when fxF2 = 50S

fxI = (foI + fB/2)OB = 42OB, when foI = 36

b. In the absence of the echo spreading and the oblique reflection in the F region, the value of fxF2 is scaled as fxI including the letters attached. In this case, the numerical value of fxF2 is used with descriptive letter X.

#### (Examples)

fxI = (fxF2) X = 49X, when fxF2 = 49

fxI = 49X, when fxF2 = 49S

fxI = 46UX, when fxF2 = 46US

fxI = fxF2 = S, when fxF2, foF2 = S

fxI = 460X, when foF2: numerical value fxF2: no numerical value

- 4. Appendix 2 (p.119 of this manual) which is extracted from the INAG Bulletin (INAG-33, pp. 32-33 May 1981) gives much more variety of examples for fxI scaling.
- Monthly tabulation sheets may be left blank for columns at hours for which spread F traces are seldom or never seen, as in the practice for E and Fl parameters (p. 102 R.H. 3.32(c)). Most groups find it more efficient to tabulate fxI at all hours.

	1		
1	Ionogram without the spread echoes (Nighttime)	fmin	16ES
	1 2 3 4 15 6 7 8 9 10 11MHz	foE	1020
km	1 2 3 4 5 6 7 8 9 10 11MHz	h'E	
400 -		foEs	60JA
		fxEs	66
300 -		h'Es	100
	Ho	Es type	f2
200 -	eren	fbEs	16ES
200	on c	foFl	
7.00		h'F	230US
100 -		h'F2	_
		foF2	43
		fxI	49X
	fmin foF2 fxF2 fxEs  The extraordinary F trace is masked by the		
2	interference	fmin	16ES
		foE	
<b>l</b> .		h¹E	
400 -		foEs	16ES
	interf	fxEs	
300 -	tt 3 1 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	h'Es	S
-	erfer,	Es type	
200 -	er	fbEs	16ES
200 -		foFl	
	erenc	h†F	250
100 -		h'F2	
		foF2	40
	4 4 1	fxI	460X
	fmin foF2 fxF2		
(3)	The spread echoes are recorded in a lower frequency		
(O)	range than foF2	fmin	10EE
		foE	20111
		h'E	
400 -		foEs	10EE
		fxEs	
300 -		h'Es	E
J - "		Es type	
200 -		fbEs	loee
ZUU -		foFl	
		h'F	210
100 -		h'F2	
		foF2	36
	0.700.770	fxI	42X
<u> </u>	foF2 fxF2		
(A)	The echo spreading is seen on both the ordinary and extraordinary F traces	fmin	11
	CV 01 MOI WINGT À 1. 01 WGES	foE	T-T-
		h'E	
400 -		foEs	31JA
700		fxEs	37 -37
-		ixes h'Es	100
300 -			fl
1		Es type fbEs	11EB
200 -			ፕፕፑይ
		foFl h'F	215
100			C1)
100 -		h'F2	46UF
		foF2	58
<u></u>	<u> </u>	fxI	20
L fi	min fxEsfoF2fxF2-fxI		

Observation: Nighttime ionogram. foF2 = 4.3 MHz, fxF2 = 4.9 MHz.

Interpretation: No echo spreading is recorded in the F trace of this ionogram. Therefore, fxI is expressed by the value of fxF2 followed by the letter X. The Es layer has no relation to the scaling of fxI.

fxI = (fxF2)X = 49X

Observation: foF2 = 4.0 MHz. The trace near fxF2 is masked by the interference.

Interpretation : fxF2 can be obtained by the extrapolation from the extraordinary trace itself. In this Case, however, deduction of fxF2 from foF2 is more practical.

fxI = (foF2 + fB/2)oS = 460X

Comment: The qualifying letter O means that the extraordinary component is obtained by means of the ordinary component.

The descriptive letter X has priority over S since no echo spreading in the F trace is seen.

Observation: Spread echoes other than the F layer trace are recorded in the frequency range from 1.6 to 3.5 MHz above the height of 300 km.

Interpretation: Such echoes do not influence on the scaling of fxI, since fxI is to be expressed by the highest frequency of the F trace. Following the same process as in Case 1, fxI = (fxF2)X = 42X

Comment: When fxF2 is expressed by a numerical value with some letters, fxI can be scaled as fxF2 itself.

fxI = fxF2 = 42US


Observation: The ordinary F trace spreads over 4.6  $\sim$  5.1 MHz, while the extraordinary trace does over 5.3  $\sim$  5.8 MHz.

Interpretation: The spreading is not so severe. In this ionogram, the inner edge (lower side of frequency) is the main trace.

The highest frequency of the extraordinary component is scaled as fxI.

fxI = 58

# fxl-2




**5**)

Observation: The echo spreading is observed over the whole frequency range of the F trace. No distinct reflection is found out of rather uniformly spread part.

Interpretation: The highest frequency of the F trace including the spread part is fxI. Therefore,

fxI = 63



Comment: A part of spread echoes is sometimes obscured by severe interference.

In this case

fxI = F, foF2 = 50DS

**(6)** 

Observation : A spread F trace is recorded together with the regular F trace with the second order reflection.

Interpretation: The trace accompanying the echo spreading at a height of 210 km is the reflection from an oblique direction from which the value of fxI is scaled.

 $fxI \approx 58$ 

Comment :

An oblique reflection tends to approach down to the virtual height of the regular F layer from a higher height at which it appeared in the beginning, and then to increase its height again until it disappears. This can be explained by assuming some irregular structure which moves horizontally when passing over a sounding station.

7

Observation: A nighttime ionogram. Only the spread trace of the F layer ordinary component is observed.

Interpretation: fmin is so high that the extraordinary component seems to be lost owing to the large absorption (B). In this case, fxI can be extrapolated from foI (the highest frequency of the spread ordinary F trace) by adding fB/2 to foI. Thus, the letters to be attached are the qualifying letter O and the descriptive letter B.

fxI = (foI + fB/2)OB = 42OB

Comment :

As for fB, see Case 7 of foEs.

If there is no echo spreading, this Case is equivalent to Case 2 in scaling fxI.

8

Observation: The F trace is normal but the spur develops from the extraordinary trace.

Interpretation : The spur has the highest frequency in this ionogram.

fxI = 60P


Comment: The spread echo attached to the extraordinary component is called "spur" because it resembles the spur in shape. This kind of echo is likely to appear when the ionosphere is severely tilted or has an irregular structure in it.

#### M factor

#### @ Definition :

The M factor (Maximum Usable Frequency Factor) is a conversion factor for obtaining the maximum frequency usable in a given oblique propagation distance from the critical frequency at vertical incidence (fo). The M factor for the standard distance of 3000 km is called M(3000) which is usually expressed with the name of reflection layers as M(3000)F2 or M(3000)F1.

M(3000) can be obtained by applying the standard transmission curve (see pp.23  $\sim$  25, R.H.) for the ground distance of 3000 km to the ordinary component of the first order reflection from the layer concerned. Practically, M(3000) is related to MUF(3000) (Maximum Usable Frequency for 3000 km path length) and fo (the ordinary wave critical frequency at vertical incidence) as below:



$$M(3000) = \frac{MUF(3000)}{fo}$$

#### @ Scaling accuracy:

Both M(3000) F2 and M(3000) F1 are scaled at the accuracy of 0.05. (e.g. 3.15 or 4.20).

#### @ Indication of scaled value :

 $\mbox{M(3000)}$  is expressed by the numerical value with or without letters, or the letter only.

#### @ Notices for scaling :

- 1. M(3000) should be scaled from the ordinary component of the F2 or F1 layers.
- 2. The qualifying and descriptive letters to be attached to M(3000)F2 or M(3000)F1 are usually the same as those for foF2 or foF1 respectively. (Examples)

M(3000)F2 = F, when foF2 = F.

M(3000)Fl = L, when foFl = L.

M(3000)F2 = 305F, when foF2 = 34F.

M(3000)F2 = 320JR, when foF2 = 44JR.

3. There are some exceptions where M(3000) accompanies different letters from what foF2 or foF1 does.

#### (Examples)

M(3000)F2 = C, when foF2 = 153DC. (No trace above 15.3 MHz)

M(3000)F2 = G, when foF2 = 42EG. (foF1 \ge foF2)

M(3000)F2 = A, when foF2 = 98. (Blanketing by Es trace as in Case 2)

M(3000)Fl = B, when foFl = 52. (Large absorption)

M(3000)Fl = Y, when foFl = 46UY. (Fl Lacuna as in Case 12 of foFl)

#### How to obtain graphically the M factor

The procedure to be followed to obtain graphically the M factor is different for the ionogram with the logarithmic frequency scale and that with the linear frequency scale.

The M factor can be read out directly from the ionogram with the logarithmic frequency scale by means of the slider (Fig.a on p.113) on which the standard transmission curve is depicted. The procedure to be followed in doing this is described in the following "Scaling practice...".


On the other hand, the procedure to obtain the M factor from the ionogram with the linear frequency scale is rather complicated. Instead of one transmission curve in the case of the logarithmic scale, a set of standard MUF curves has to be prepared from the standard transmission curve. The MUF curve which just touches the trace gives the MUF. The M factor is obtained by dividing this MUF by the critical frequency of the trace.


This Manual illustrates the Cases for scaling the M factor from the ionograms with the logarithmic frequency scale.

Scaling practice of the M factor from the ionogram with logarithmic frequency scale

- 1. A transparent slider (Fig.a on p.113) on which the standard transmission curve for 3000 km is depicted should be prepared. The shape of the standard transmission curve is defined by the table given on page 23 of R.H.
- 2. The slider is laid over the ionogram so that both the height scales coincide with each other.
- 3. The slider is moved until the transmission curve touches the outer edge of the reflection from the layer concerned as shown in Fig.b on page 113(For details, see pp.23-24 and p.78 of R.H.).
- 4. Thus a value on the M factor scale (arrow in the Figure) corresponding to the critical frequency of the layer on the ionogram can be read out.


  This value is the M factor.
- 5. The frequency which coincides with 1 on the M factor scale is the MUF.
- 6. The procedure mentioned above is also applicable to the Fl layer trace.





( b ) Use of M factor slider

# M factor -1



#### M factor - 1

1)

Observation: A typical ionogram in summer daytime. Traces for both F2 and F1 layers are recorded very clearly.

foF1 = 52, foF2 = 82.

Interpretation:

Both M(3000)F2 and M(3000)F1 can be scaled by fitting the transmission curves (dash-dot curves) to the F2 and F1 traces respectively.

M(3000)F2 = 315

M(3000)F1 = 355

2

Observation: As far as the F region reflection is concerned, both foF2 and fxF2 can be scaled by numerical values only, although the trace below 9.7 MHz is blanketed by the Es layer.

Interpretation: Since the curved parts of the F2 and F1 traces are blanketed by the Es layer, both the M factors are expressed by the letter A.

M(3000) F2 = A

M(3000) F1 = A

Comment :



In an example as shown in the left figure, foFl can be scaled, whereas the lower part of Fl trace is blanketed.

M(3000) F1 = A

(3)

Observation: A nighttime ionogram. In the F region, the extraordinary component is clearly observed, while the ordinary one is lost.

Interpretation: First of all, foF2 is deduced from fxF2.

foF2 = (fxF2 - fB/2)JR = 44JR

Then the ordinary wave trace is reproduced imaginarily as the dotted curve to which the transmission curve is applied. M(3000)F2 should have the same letters as foF2 in this Case.

M(3000)F2=330JR

Comment: If the cause of the disappearance of the ordinary F trace is the interference, the letter R is replaced by the letter S.

(4

Observation: No F2 trace is recorded.


Interpretation: The trace in the F region is the F1 trace. The F2 layer is in the so-called G condition where foF2 decreases down to foF1 or lower value (see Case 5 of foF2).

M(3000) F2 = G

M(3000) F1 = 345

Comment: It is very important in interpreting the G condition to take into account the progress of ionospheric disturbances and the sequential variation of foF2 and h'F2, because the G condition may be confused with the case for which the letter W should be applied.

# M factor -2



M factor - 2 5 Observation: Since the cusp of foFl is not clear, it is scaled as foF1 = L (55). The F2 layer is normal. M(3000)F2 is scaled easily, whereas there is no tangen-Interpretation: tial point on the Fl trace to the transmission curve. Therefore, M(3000)Fl is expressed only by the letter L. M(3000)F2 = 310 M(3000)F1 = LObservation : A nighttime ionogram. 6 The frequency-type spreading is foF2 = 34Fobserved. The inner edge (lower side of frequency) of the trace Interpretation : is clear. The M factor is scaled by applying the transmission curve to the clear ordinary trace. pressed by attaching the descriptive letter F to the numerical value. M(3000) F2 = 320F Comment : The second order reflection is conveniently used in identifying the ordinary component trace, since it is likely to be observed more clearly (without the spreading) than the first. The F trace is spread over a fairly wide frequency range. Observation: 7 The outer edge of the trace is clear. Interpretation : The clear edge is interpreted as the extraordinary fxF2 = 4.4 MHzcomponent. Since the ordinary component can be inferred from the extraordinary one, the M factor is to be scaled by fitting the transmission curve to the ordinary component trace in-M(3000)F2 is expressed by applying the qualifying letter J and the descriptive letter F. M(3000)F2 = 305JFComment : The width of echoes should not be overlooked in fitting the transmission curve even to the inferred trace. In other words. the curve is adjusted so as to touch the outer edge of the inferred trace. Similar caution should be paid to Case 3 and Case 6. 8 Observation : .. The F trace above 16.7 MHz is not recorded. frequency width of trace to be extrapolated does not seem to exceed 20% of foF2 (see Case 10 of foF2). Interpretation: Since foF2 is scaled with the qualifying letter D (greater), M(3000)F2 is expressed by only the letter which describes the reason for the disappearance of the trace.

Concerning M(3000)Fl, the situation is same as Case 5.

M(3000) F2 = R

M(3000) Fl = L

# Appendix 1

lonograms frequently show multiple and mixed reflections. (R.H. pp.15-17)

A multiple reflection is the name given to a trace which has been reflected from the ionosphere more than once. An echo which results from two reflections from the same layer, with an intermediate reflection from the ground, is called a second order; three reflections give a third order, and so on. Orders as high as fifteen or more occasionally occur when absorption is extremely low. These very high orders are still being reflected between the ground and the ionosphere after a time greater than that of the time base period and consequently appear on the ionogram. Fig. 1.9(b) shows a typical example of these 'round-the-time-base' traces, orders 8 to 11 are visible.

It is possible for mixed reflections between the E and F layers to occur when sporadic E is present. The most common of these is a second order reflection from the top of a sporadic E layer - the M reflection at a height (2h'F-h'Es). The mixed mode F reflection followed by Es reflection, or vice versa, are also common at a height (h'F + h'Es). Both are shown in Fig. 1.9(c). The M reflection often gives a stronger trace than the 2F normal mode when absorption is present, as it has only passed through the absorbing D region twice instead of four times. Higher multiples also occur and can be easily identified by noting that the M and N traces are a constant distance (h'Es) from the 2F and 1F traces, respectively. Higher modes 2F + E, 3F - E, etc., are identified similarly. A typical ionogram showing E, F and mixed mode multiple reflection is shown in Fig. 1.9(d) together with the mode identifications.

Under normal circumstances, M and N reflections are not scaled but can be used occasionally to give a numerical value of foF2 when the layer is tilted so that the normal F traces are missing.




Fig. 1.9(b) Ionogram showing very high order F region reflections, also multiple reflections.

Arrows indicate 'round-the-time-base' traces.

#### Paths of M and N reflections




Fig. 1.9(c) Virtual height of M reflection 2F-Es, N reflection F+Es.

# Appendix 2 (INAG Bulletin No. 33, pp.32-33)

# SPREAD F AND fx/ SCALING

			<u></u>
1	2	3	4
	ىرىر		
5	6	7 	8
9	10	11	12
13	14	15	16
17	18	19	20
			<u></u>
21	22	23 2nd January 1st	24

SPREAD - F	INTERFERENCE

Ex.	foF2	fxI	h'F	Comment
1	044	050-X	250	Normal ionogram
2	044-H	050-X	250	No scatter present priority X on fxI
3	044	050-X	250	No scatter present, priority X on fxI
4	038EG	044-X	250	F2 region in G condition, fxI ≡ fxF1
5	044	0500X	250	fxI determined from o mode, priority X on fxI
6	044	0500X	250	fxI determined from o mode, priority X on fxI
7	010	016	250	fxF2 not seen as close to gyro-frequency
8 9	A	Α	A	Complete blanketing by Sporadic E
9	044-F	053	250	Spread-F exceeds 0.3MHz; -F on fxI optional
10	044~F	057	250	More severe Spread-F than 9 but scaling similar different degree of Spread-F on o and x traces
11	044-F	0540B	250	fxI value determined from foI
12	044-F	0560B	250	More severe Spread F than 11 but similar scaling
13	044DF or F	060	250	Very severe Spread-F; resolution of o and x- traces not possible
14	044-F	05305	250	<pre>fxI = foI + fB/2, with descriptive letter for interference</pre>
15	044JS	053-F	250	foF2 = fxF2 - fB/2, Presence of Spread-F indicated on fx1
16	038DS	F	250	F given priority over other letters in fxI to show presence of Spread-F
17	044	053-X	250-Q	Simple range spread; no frequency spread hence -X
18	044	050-X	250-Q	Different form of range spread
19	044-F	058-Q	250-Q	fxI value determined from range spread structure
20	044	070-P	250	Polar spur gives fxI value
21	044-F	070-P	250	Polar spur gives fxl value
22	F	070	Q	Extensive mixed spread present
23	044	050-X		Ground backscatter trace, not used to evaluate fxI
24	В	В	В	Complete absorption

#### POSTSCRIPT

The original edition of this Manual was completed by H. Ohyama in 1980 for the training of young specialists of ionogram scalings. The publication of this Training Manual was announced by N. Wakai, the Japanese INAG representative, at the INAG meeting which was held in Geneva on the occasion of CCIR Study Group Meeting in June to July 1980.

Mr. W. R. Piggott, the chairman of INAG, encouraged him to translate the

After one year experience by the experts at local Radio Wave Observatories, Radio Research Laboratories, the revised edition in Japanese was published by H. Ohyama and T. Koizumi in March 1981 for domestic use in

Since then the translation has been made by a small group in RRL.

The wording in English might not necessarily be consistent with the Ionogram Handbook and its revised Edition. The philosophy of interpretation, however, should be same. Comments by the INAG members as well as the users on expressions and scaling procedures in this Manual are highly invited.

We wish to express many thanks to Miss Y. Nagano for her assistance through the typewriting.

March, 1985

Japan.

Manual written in Japanese into English.

Noboru WAKAI 左井 登 Haruo OHYAMA 大山治男 Tokuji KOIZUMI 小泉德次 Radio Research Laboratories Koganei-shi, Tokyo 184 JAPAN Tel.) 0423-21-1211

Telex) 2832611 DEMPA J

#### POSTSCRIPT FOR REVISED EDITION

Reorganization of RRL was effective on April 8, 1985, just after the publication of the first edition of this Manual. The research section responsible for the revision work of the Manual was transferred to Ionospheric Observation Section, Technical Information Division from Radio Wave Division. Revised texts and re-drawn figures were prepared at the section with the assistance by Mrs. R. Nemugaki.

Requests of additional copies and comments on the content of the Manual are invited to send to the following address:

Ionospheric Observation Section Technical Information Division Radio Research Laboratory

Nukui-Kitamachi 4-2-1, Koganei-shi, Tokyo 184 JAPAN

Telephone: 0423-21-1211 Telex: 2832611 DEMPA J Facsimile: 0423-24-9061

July, 1986

- N. Wakai
- H. Ohyama
- T. Koizumí

Radio Research Laboratory

#### POSTSCRIPT FOR THIRD VERSION

Requests of additional copies and comments on the content of the Manual are invited to send to the following address:

Ionospheric Observation Section Technical Information Division Radio Research Laboratory

Nukui-Kitamachi 4-2-1 Koganei-shi, Tokyo 184 JAPAN

Telephone: 0423-21-1211 Telex: 2832611 DEMPA J Facsimile: 0423-24-9061

October 1987

Present address of the authors for contact.

- N. Wakai, Professor, Institute of Research and Development,
  Tokai University,
  Tomigaya, Shibuya-ku, Tokyo 151
- H. Ohyama | Radio Research Laboratory
- T. Koizumi